

屋内照明器具特性

品番 (品名)	LGB51210														
光源	LED5000_70_538 x1 538.0 lm														
管理番号	K0154735(0)DB1														
BZ分類	BZ6/0.7/BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	16%																			
下方光束	84%																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.69 中 0.67 否 0.63	0.6	53	40	32	27	51	39	32	27	47	37	30	26	43	35	29	25	22	
		0.8	62	50	42	36	60	49	41	36	55	46	39	34	51	43	38	33	30	
		1.0	68	57	49	43	66	56	48	43	61	52	46	41	56	49	44	39	35	
		1.25	74	64	56	50	71	62	55	49	66	58	52	47	61	55	50	46	41	
下方投影面積 等価発光面積	c m ²	1.5	78	69	62	56	75	67	60	55	70	63	57	52	65	59	54	50	46	
		2.0	84	76	70	64	81	74	68	63	75	69	64	60	70	65	61	57	52	
		2.5	88	81	75	70	85	78	73	68	79	74	69	65	73	69	66	62	57	
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
H m	1.35 H m	1.23 H m	4.0	93	88	84	80	90	86	82	78	85	81	78	74	79	76	73	71	65
			5.0	95	91	87	84	92	89	85	82	87	84	81	78	81	79	76	74	68
			7.0	98	95	92	89	95	92	89	87	89	87	84	82	84	82	80	78	72
			10.0	100	97	95	93	97	94	92	91	91	89	88	86	86	84	83	82	75

