

屋内照明器具特性

品番 (品名)	XLX180RKN														
光源	LED5000_85_7000 x1 7000.0 lm														
管理番号	K0161221(0)D 1														
BZ分類	BZ4/0.7/BZ3														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01) ZCM																		
下方光束	100%																				
保守率	良 中 否	0.81	0.6	61	50	43	38	60	49	43	38	58	48	42	38	56	47	42	37	36	
		0.77	0.8	72	61	54	49	70	61	54	49	68	59	53	49	65	58	53	49	47	
			1.0	78	69	62	57	77	68	62	57	74	67	61	57	72	65	60	56	54	
		0.68	1.25	84	76	69	65	83	75	69	64	80	73	68	64	77	72	67	63	61	
下方投影面積	c m ²	1.5	88	80	75	70	86	79	74	70	84	78	73	69	81	76	72	68	66		
		2.0	93	87	82	78	91	86	81	77	89	84	80	76	86	82	79	76	73		
等価発光面積	c m ²	2.5	96	91	86	83	94	90	86	82	92	88	84	81	89	86	83	80	78		
		3.0	98	94	90	86	97	93	89	86	94	90	87	85	91	89	86	84	81		
取付高さ	器具間隔最大限		4.0	101	97	94	91	99	96	93	91	97	94	92	89	94	92	90	88	86	
	横方向 (A)	縦方向 (B)	5.0	102	99	97	94	101	98	96	94	98	96	94	92	96	94	92	91	88	
1.5m	1.9m	1.9m	7.0	104	102	100	98	103	101	99	97	100	99	97	96	98	96	95	94	91	
2	2.52	2.52	10.0	105	104	102	101	104	103	101	100	102	100	99	98	99	98	97	97	94	
2.5	3.15	3.15																			
3	3.78	3.78																			

