

# 屋内照明器具特性

|         |                    |  |  |  |  |          |  |  |  |  |
|---------|--------------------|--|--|--|--|----------|--|--|--|--|
| 品番 (品名) | LGB51321           |  |  |  |  |          |  |  |  |  |
| 光源      | LED3500_70_1025 x1 |  |  |  |  | 1025.0lm |  |  |  |  |
| 管理番号    | K0154734(0)DB1     |  |  |  |  |          |  |  |  |  |
| BZ分類    | BZ6/0.7/BZ5        |  |  |  |  |          |  |  |  |  |

|        |               |         |      |     |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    |     |
|--------|---------------|---------|------|-----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|----|-----|
| 器具効率   | 100%          | 天井      | 80%  |     |    |     | 70% |    |    |     | 50% |    |    |     | 30% |    |    |     | 0% |    |     |
|        | 上方光束          |         | 16%  | 反射率 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30 | 10 | 0%  |
|        | 下方光束          |         | 84%  |     | 床  | 10% |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |    |    |     |
| 室指数    | 照明率 ( X0.01 ) |         |      |     |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |    | ZCM |
| 保守率    | 良             | 0.69    | 0.6  | 53  | 40 | 33  | 27  | 51 | 39 | 32  | 27  | 47 | 37 | 30  | 26  | 43 | 35 | 29  | 25 | 22 |     |
|        | 中             | 0.67    | 0.8  | 62  | 50 | 42  | 36  | 60 | 49 | 41  | 36  | 55 | 46 | 39  | 34  | 51 | 43 | 37  | 33 | 30 |     |
|        | 否             | 0.63    | 1.0  | 69  | 57 | 49  | 43  | 66 | 56 | 48  | 43  | 61 | 52 | 46  | 41  | 56 | 49 | 44  | 39 | 35 |     |
|        |               |         | 1.25 | 74  | 64 | 57  | 51  | 72 | 62 | 55  | 50  | 66 | 58 | 52  | 48  | 61 | 55 | 50  | 46 | 41 |     |
| 下方投影面積 |               |         | 1.5  | 79  | 69 | 62  | 56  | 76 | 67 | 60  | 55  | 70 | 63 | 57  | 53  | 65 | 59 | 54  | 50 | 45 |     |
|        |               |         | 2.0  | 84  | 76 | 70  | 64  | 81 | 74 | 68  | 63  | 75 | 69 | 64  | 60  | 70 | 65 | 61  | 57 | 52 |     |
| 取付高さ   | 器具間隔最大限       |         | 2.5  | 88  | 81 | 75  | 70  | 85 | 78 | 73  | 68  | 79 | 74 | 69  | 65  | 74 | 69 | 66  | 62 | 57 |     |
|        | 横方向 (A)       | 縦方向 (B) | 3.0  | 90  | 84 | 79  | 74  | 87 | 82 | 77  | 73  | 81 | 77 | 73  | 69  | 76 | 72 | 69  | 66 | 60 |     |
| 1.5m   | 2.05m         | 1.88m   | 4.0  | 94  | 89 | 84  | 80  | 91 | 86 | 82  | 78  | 85 | 81 | 78  | 75  | 79 | 76 | 73  | 71 | 65 |     |
| 2      | 2.72          | 2.48    | 5.0  | 96  | 91 | 88  | 84  | 93 | 89 | 85  | 82  | 87 | 84 | 81  | 78  | 81 | 79 | 76  | 74 | 68 |     |
| 2.5    | 3.41          | 3.09    | 7.0  | 98  | 95 | 92  | 89  | 95 | 92 | 89  | 87  | 89 | 87 | 85  | 82  | 84 | 82 | 80  | 78 | 72 |     |
| 3      | 4.07          | 3.7     | 10.0 | 100 | 98 | 95  | 93  | 97 | 95 | 93  | 91  | 91 | 89 | 88  | 86  | 86 | 84 | 83  | 82 | 75 |     |

