

# 屋内照明器具特性

|         |                   |  |  |  |  |          |  |  |  |  |
|---------|-------------------|--|--|--|--|----------|--|--|--|--|
| 品番 (品名) | LGB51326          |  |  |  |  |          |  |  |  |  |
| 光源      | LED3500_70_765 x1 |  |  |  |  | 765.0 lm |  |  |  |  |
| 管理番号    | K0154733(0)DB1    |  |  |  |  |          |  |  |  |  |
| BZ分類    | BZ5/0.7/BZ4       |  |  |  |  |          |  |  |  |  |

|        |               |         |      |     |     |     |     |     |     |     |     |     |    |     |     |    |    |     |    |    |     |
|--------|---------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|-----|----|----|-----|----|----|-----|
| 器具効率   | 100%          | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |    |     | 30% |    |    |     | 0% |    |     |
|        | 上方光束          |         | 0%   | 反射率 | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70 | 50  | 30  | 10 | 70 | 50  | 30 | 10 | 0%  |
|        | 下方光束          |         | 100% |     | 床   | 10% |     |     |     | 10% |     |     |    | 10% |     |    |    | 10% |    |    |     |
| 室指数    | 照明率 ( X0.01 ) |         |      |     |     |     |     |     |     |     |     |     |    |     |     |    |    |     |    |    | ZCM |
| 保守率    | 良             | 0.69    | 0.6  | 58  | 46  | 38  | 33  | 56  | 45  | 38  | 33  | 54  | 44 | 37  | 32  | 52 | 43 | 37  | 32 | 30 |     |
|        | 中             | 0.67    | 0.8  | 68  | 57  | 49  | 43  | 66  | 56  | 49  | 43  | 64  | 54 | 48  | 43  | 61 | 53 | 47  | 43 | 41 |     |
|        | 否             | 0.63    | 1.0  | 74  | 64  | 57  | 51  | 73  | 63  | 56  | 51  | 70  | 62 | 55  | 50  | 67 | 60 | 55  | 50 | 48 |     |
|        |               |         | 1.25 | 80  | 71  | 64  | 59  | 79  | 70  | 64  | 58  | 76  | 68 | 63  | 58  | 73 | 67 | 62  | 57 | 55 |     |
| 下方投影面積 |               |         | 1.5  | 85  | 76  | 69  | 64  | 83  | 75  | 69  | 64  | 80  | 73 | 68  | 63  | 77 | 71 | 67  | 63 | 60 |     |
|        | 等価発光面積        |         | 2.0  | 90  | 83  | 77  | 73  | 89  | 82  | 77  | 72  | 85  | 80 | 75  | 71  | 83 | 78 | 74  | 70 | 68 |     |
| 取付高さ   | 器具間隔最大限       |         | 2.5  | 94  | 88  | 83  | 78  | 92  | 86  | 82  | 78  | 89  | 84 | 80  | 77  | 86 | 82 | 79  | 76 | 73 |     |
|        | 横方向 (A)       | 縦方向 (B) | 3.0  | 96  | 91  | 86  | 82  | 94  | 90  | 85  | 82  | 92  | 87 | 84  | 81  | 89 | 85 | 82  | 80 | 77 |     |
| 1.5m   | 1.84m         | 1.89m   | 4.0  | 99  | 95  | 91  | 88  | 98  | 94  | 90  | 87  | 95  | 91 | 89  | 86  | 92 | 89 | 87  | 85 | 82 |     |
| 2      | 2.45          | 2.49    | 5.0  | 101 | 97  | 94  | 92  | 99  | 96  | 93  | 91  | 97  | 94 | 92  | 89  | 94 | 92 | 90  | 88 | 85 |     |
| 2.5    | 3.08          | 3.1     | 7.0  | 103 | 100 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97 | 95  | 93  | 96 | 95 | 93  | 92 | 89 |     |
| 3      | 3.69          | 3.72    | 10.0 | 104 | 103 | 101 | 99  | 103 | 102 | 100 | 98  | 101 | 99 | 98  | 97  | 98 | 97 | 96  | 95 | 92 |     |

