


屋内照明器具特性	
品番 (品名)	NND26411K
光源	LEDRGB_70_1.8 x1 1.8 1m
管理番号	K0164051(0)DR1
BZ分類	BZ10

器具効率	100%	反射率	天井	80%				70%				50%				30%				0%
	上方光束 99%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束 1%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.69	0.6	43	33	26	22	37	28	23	19	25	19	16	13	14	11	9	8	0
	中	0.67	0.8	51	41	34	29	43	35	29	25	29	24	21	18	17	14	12	10	0
	否	0.63	1.0	56	47	40	35	48	40	35	31	33	28	24	22	19	16	14	13	0
				1.25	61	53	46	41	52	46	40	36	36	31	28	25	20	18	16	15
下方投影面積			1.5	65	57	51	46	56	49	44	40	38	34	31	28	22	20	18	17	0
	等価発光面積		2.0	70	63	58	54	60	55	50	47	41	38	35	33	24	22	21	19	0
取付高さ	器具間隔最大限		2.5	73	67	63	59	63	58	54	51	43	40	38	36	25	23	22	21	0
	横方向 (A)	縦方向 (B)	3.0	75	70	66	62	65	61	57	54	45	42	40	38	26	24	23	22	0
Hm	0.20Hm	0.20Hm	4.0	78	74	70	67	67	64	61	58	46	44	43	41	27	26	25	24	0
			5.0	80	76	73	71	69	66	63	61	47	46	44	43	28	27	26	25	0
			7.0	82	79	77	75	70	68	66	65	49	48	46	45	28	28	27	27	0
			10.0	83	81	79	78	72	70	69	67	50	49	48	47	29	29	28	28	0



直射水平面照度	80 lx																			
	60																			
	40																			
	20																			
	10																			
	8																			
	6																			
	4																			
	2																			
	.8																			
	.6																			
	.4																			
	.2																			
		8m	6	4	2	0	2	4	6	8										