

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | XLGB81847                  |
| 光源       | LED2700_70_685 ×1 685.0 lm |
| 管理番号     | K0169187 ( 0 ) DR 1        |
| BZ分類     | BZ5                        |

| 器具効率     |           | 100 %<br><br>上方光束<br>99 %<br>下方光束<br>1 % | 反射率    | 天井   | 80 %            |     |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|-----------|------------------------------------------|--------|------|-----------------|-----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |           |                                          |        | 壁    | 70              | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |           |                                          |        | 床    | 10 %            |     |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |           |                                          |        | 室指数  | 照明率 ( X0.01 )   |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |           | 良<br>中<br>否                              | 0.67   | 0.6  | 43              | 33  | 26 | 22 | 37   | 28 | 23 | 19 | 25   | 20 | 16 | 13 | 14   | 11 | 9  | 8  | 0   |
|          |           |                                          | 0.63   | 0.8  | 51              | 41  | 34 | 29 | 43   | 35 | 30 | 25 | 30   | 24 | 21 | 18 | 17   | 14 | 12 | 11 | 0   |
|          |           |                                          | 0.56   | 1.0  | 56              | 47  | 40 | 35 | 48   | 41 | 35 | 31 | 33   | 28 | 25 | 22 | 19   | 16 | 14 | 13 | 0   |
|          |           |                                          |        | 1.25 | 61              | 53  | 47 | 42 | 53   | 46 | 40 | 36 | 36   | 32 | 28 | 26 | 21   | 18 | 17 | 15 | 0   |
| 下方投影面積   |           | cm <sup>2</sup>                          |        | 1.5  | 65              | 57  | 51 | 47 | 56   | 50 | 45 | 41 | 38   | 34 | 31 | 29 | 22   | 20 | 18 | 17 | 0   |
|          |           |                                          | 等価発光面積 |      | cm <sup>2</sup> | 2.0 | 70 | 64 | 58   | 54 | 60 | 55 | 50   | 47 | 41 | 38 | 35   | 33 | 24 | 22 | 21  |
| 取付<br>高さ | 器具間隔最大限   |                                          | 2.5    | 73   | 68              | 63  | 59 | 63 | 58   | 54 | 51 | 43 | 41   | 38 | 36 | 25 | 24   | 23 | 21 | 0  |     |
|          | 横方向 ( A ) | 縦方向 ( B )                                | 3.0    | 75   | 70              | 66  | 63 | 65 | 61   | 57 | 54 | 45 | 42   | 40 | 38 | 26 | 25   | 24 | 23 | 0  |     |
| H m      | 1.15 H m  | 1.34 H m                                 | 4.0    | 78   | 74              | 71  | 68 | 67 | 64   | 61 | 59 | 47 | 45   | 43 | 41 | 27 | 26   | 25 | 24 | 0  |     |
|          |           |                                          | 5.0    | 80   | 76              | 74  | 71 | 69 | 66   | 64 | 62 | 48 | 46   | 45 | 43 | 28 | 27   | 26 | 26 | 0  |     |
|          |           |                                          | 7.0    | 82   | 79              | 77  | 75 | 70 | 69   | 67 | 65 | 49 | 48   | 47 | 46 | 29 | 28   | 28 | 27 | 0  |     |
|          |           |                                          | 10.0   | 83   | 81              | 80  | 78 | 72 | 70   | 69 | 68 | 50 | 49   | 48 | 48 | 29 | 29   | 29 | 28 | 0  |     |

