

# 屋内照明器具特性

品番 (品名)	LGB16403K									
光源	LDA4 WW- H- E17 / S / 4 ×1					440.0 lm				
管理番号	K0187031 ( 0 ) DB 1									
BZ分類	BZ5 / 0.7 / BZ6									

器具効率	86 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		23 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		63 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.67	0.6	45	34	28	23	42	33	27	22	38	30	25	21	34	28	23	20	16	
	中	0.63	0.8	51	41	34	29	49	39	33	28	44	36	30	26	39	33	28	25	21	
	否	0.56	1.0	56	46	39	34	53	44	38	33	48	40	35	31	43	37	32	28	24	
			1.25	61	51	44	39	57	49	43	38	51	45	39	35	46	40	36	32	27	
下方投影面積			c m <sup>2</sup>	1.5	64	55	49	43	61	53	47	42	54	48	43	39	49	43	39	36	30
	等価発光面積		c m <sup>2</sup>	2.0	69	61	55	50	65	58	53	48	58	53	48	44	52	48	44	41	34
取付高さ	器具間隔最大限			2.5	72	65	59	54	68	62	57	52	61	56	52	48	55	51	48	44	38
		横方向 ( A )	縦方向 ( B )	3.0	74	68	63	58	70	65	60	56	63	59	55	52	57	53	50	47	40
H m	1.03 H m	1.03 H m		4.0	77	72	67	63	73	69	65	61	66	63	59	56	60	57	54	52	44
				5.0	79	74	70	67	75	71	68	64	68	65	62	59	62	59	57	54	47
				7.0	81	78	74	71	77	74	71	69	70	68	66	63	64	62	60	58	50
				10.0	83	80	78	75	79	77	75	72	72	70	69	67	66	64	63	61	53

