

屋内照明器具特性

品番 (品名)	LGB85046									
光源	LED3500_70_800 x1					800.0 lm				
管理番号	K0140471(0)DB1									
BZ分類	BZ6/0.7/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%					
	上方光束		17%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
	下方光束		83%		床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																				ZCM			
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6				
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6				
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56				
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56				
下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0				
	等価発光面積																							
取付高さ	器具間隔最大限																							
	横方向 (A)	縦方向 (B)																						
1.5m	2.12m	1.86m	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0		
2	2.83	2.46	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	5.0	7.0	10.0	
2.5	3.53	3.08	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0	7.0	10.0
3	4.24	3.69	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0

