

屋内照明器具特性	
品番 (品名)	XLX800RHVC
光源	LED3500_85_9030 x1 9030.0 lm
管理番号	K0128266(3)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.81 0.77 0.68	0.6	5.6	4.3	3.5	3.0	5.4	4.3	3.5	3.0	5.2	4.2	3.5	3.0	5.0	4.1	3.4	3.0	2.8	
		0.8	6.6	5.4	4.6	4.0	6.4	5.3	4.6	4.0	6.2	5.2	4.5	4.0	5.9	5.1	4.4	4.0	3.8	
		1.0	7.3	6.2	5.4	4.8	7.1	6.1	5.3	4.8	6.8	5.9	5.3	4.7	6.5	5.8	5.2	4.7	4.5	
		1.25	7.9	6.9	6.1	5.6	7.7	6.8	6.1	5.5	7.4	6.6	6.0	5.5	7.1	6.4	5.9	5.4	5.2	
下方投影面積	cm <sup>2</sup>	1.5	8.3	7.4	6.7	6.1	8.1	7.3	6.6	6.1	7.8	7.1	6.5	6.0	7.5	6.9	6.4	6.0	5.7	
		2.0	8.9	8.1	7.5	7.0	8.7	8.0	7.4	7.0	8.4	7.8	7.3	6.9	8.1	7.6	7.2	6.8	6.6	
取付高さ	器具間隔最大限		2.5	9.3	8.6	8.1	7.6	9.1	8.5	8.0	7.6	8.8	8.3	7.8	7.5	8.5	8.1	7.7	7.4	7.1
	横方向 (A)	縦方向 (B)	3.0	9.5	8.9	8.5	8.0	9.3	8.8	8.4	8.0	9.1	8.6	8.2	7.9	8.8	8.4	8.1	7.8	7.5
1.5m	2.13m	2.89m	4.0	9.8	9.4	9.0	8.7	9.7	9.3	8.9	8.6	9.4	9.1	8.7	8.5	9.1	8.8	8.6	8.3	8.1
2	2.77	3.32	5.0	10.0	9.7	9.3	9.0	9.9	9.5	9.2	9.0	9.6	9.3	9.1	8.8	9.3	9.1	8.9	8.7	8.4
2.5	3.41	3.82	7.0	10.3	10.0	9.7	9.5	10.1	9.9	9.6	9.4	9.8	9.6	9.4	9.3	9.6	9.4	9.3	9.1	8.8
3	4.06	4.36	10.0	10.4	10.2	10.0	9.9	10.3	10.1	9.9	9.8	10.0	9.9	9.7	9.6	9.8	9.7	9.5	9.4	9.1

