

屋内照明器具特性

品番 (品名)	XND1031PN														
光源	LED5000_85_610 x1 610.0 lm														
管理番号	K0159508(2)DB1														
BZ分類	BZ5/0.7/BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	0%	室指数																		
下方光束	100%	照明率 (X0.01) ZCM																		
保守率	良 中 否	0.83	0.6	5.8	4.6	3.8	3.3	5.7	4.5	3.8	3.3	5.4	4.4	3.8	3.3	5.2	4.3	3.7	3.3	3.1
		0.81	0.8	6.8	5.7	4.9	4.4	6.7	5.6	4.9	4.4	6.4	5.5	4.8	4.3	6.2	5.4	4.8	4.3	4.1
		0.77	1.0	7.5	6.4	5.7	5.1	7.3	6.4	5.7	5.1	7.0	6.2	5.6	5.1	6.8	6.1	5.5	5.0	4.8
			1.25	8.1	7.1	6.4	5.9	7.9	7.0	6.4	5.9	7.6	6.9	6.3	5.8	7.3	6.7	6.2	5.8	5.5
下方投影面積	c m ²	1.5	8.5	7.6	7.0	6.4	8.3	7.5	6.9	6.4	8.0	7.3	6.8	6.3	7.7	7.2	6.7	6.3	6.1	
		2.0	9.0	8.3	7.7	7.3	8.9	8.2	7.7	7.2	8.6	8.0	7.5	7.1	8.3	7.8	7.4	7.1	6.8	
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.2	7.8	9.2	8.6	8.2	7.8	8.9	8.4	8.0	7.7	8.6	8.2	7.9	7.6	7.3
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.6	8.2	9.4	9.0	8.5	8.2	9.2	8.7	8.4	8.1	8.9	8.5	8.2	8.0	7.7
H m	1.23 H m	1.23 H m	4.0	9.9	9.5	9.1	8.8	9.7	9.4	9.0	8.7	9.5	9.1	8.9	8.6	9.2	8.9	8.7	8.5	8.2
			5.0	10.1	9.7	9.4	9.1	9.9	9.6	9.3	9.1	9.7	9.4	9.1	8.9	9.4	9.2	9.0	8.8	8.5
			7.0	10.3	10.0	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.6	9.5	9.3	9.2	8.9
			10.0	10.4	10.3	10.1	9.9	10.3	10.1	10.0	9.8	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

