

# 屋内照明器具特性

品番 (品名)	XND1051PV														
光源	LED3500_85_680 x1 680.0 l m														
管理番号	K0163222 (0) DB 1														
BZ分類	BZ4														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 ( X0.01 )															ZCM		
保守率	良	0.83	0.6	58	47	39	34	57	46	39	34	55	45	38	34	53	44	38	34	32
	中	0.81	0.8	69	58	50	45	67	57	50	44	65	56	49	44	62	54	48	44	42
	否	0.77	1.0	75	65	58	52	74	64	57	52	71	63	57	52	68	61	56	51	49
			1.25	81	72	65	60	80	71	65	59	77	69	64	59	74	68	63	59	56
下方投影面積	c m <sup>2</sup>		1.5	85	77	70	65	84	76	70	65	81	74	69	64	78	72	68	64	61
			2.0	91	84	78	73	89	83	77	73	86	81	76	72	83	79	75	71	69
取付高さ	器具間隔最大限		2.5	94	88	83	79	92	87	82	78	89	85	81	77	87	83	79	76	74
	横方向 (A)	縦方向 (B)	3.0	96	91	87	83	95	90	86	82	92	88	84	81	89	86	83	80	78
H m	1.21 H m	1.21 H m	4.0	99	95	92	88	98	94	91	88	95	92	89	86	92	90	87	85	82
			5.0	101	98	95	92	100	96	94	91	97	94	92	90	94	92	90	88	86
			7.0	103	101	98	96	102	99	97	95	99	97	95	94	97	95	93	92	89
			10.0	105	103	101	99	103	102	100	99	101	99	98	97	98	97	96	95	92

