

屋内照明器具特性

| | | | | | |
|---------|----------------|----|-------|----|--|
| 品番 (品名) | XND0651PW | | | | |
| 光源 | LED4000_85_385 | x1 | 385.0 | lm | |
| 管理番号 | K0163222(0)DB1 | | | | |
| BZ分類 | BZ4 | | | | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------|-----------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|-----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 0% | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 下方光束 | 100% | 床 | | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 室指数 | | | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.83 | 0.6 | 58 | 47 | 39 | 34 | 57 | 46 | 39 | 34 | 55 | 45 | 38 | 34 | 53 | 44 | 38 | 34 | 32 |
| | 中 | 0.81 | 0.8 | 69 | 58 | 50 | 45 | 67 | 57 | 50 | 44 | 65 | 56 | 49 | 44 | 62 | 54 | 48 | 44 | 42 |
| | 否 | 0.77 | 1.0 | 75 | 65 | 58 | 52 | 74 | 64 | 57 | 52 | 71 | 63 | 57 | 52 | 68 | 61 | 56 | 51 | 49 |
| | | | 1.25 | 81 | 72 | 65 | 60 | 80 | 71 | 65 | 59 | 77 | 69 | 64 | 59 | 74 | 68 | 63 | 59 | 56 |
| 下方投影面積 | | cm ² | 1.5 | 85 | 77 | 70 | 65 | 84 | 76 | 70 | 65 | 81 | 74 | 69 | 64 | 78 | 72 | 68 | 64 | 61 |
| 等価発光面積 | | cm ² | 2.0 | 91 | 84 | 78 | 73 | 89 | 83 | 77 | 73 | 86 | 81 | 76 | 72 | 83 | 79 | 75 | 71 | 69 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 94 | 88 | 83 | 79 | 92 | 87 | 82 | 78 | 89 | 85 | 81 | 77 | 87 | 83 | 79 | 76 | 74 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 96 | 91 | 87 | 83 | 95 | 90 | 86 | 82 | 92 | 88 | 84 | 81 | 89 | 86 | 83 | 80 | 78 |
| Hm | 1.21Hm | 1.21Hm | 4.0 | 99 | 95 | 92 | 88 | 98 | 94 | 91 | 88 | 95 | 92 | 89 | 86 | 92 | 90 | 87 | 85 | 82 |
| | | | 5.0 | 101 | 98 | 95 | 92 | 100 | 96 | 94 | 91 | 97 | 94 | 92 | 90 | 94 | 92 | 90 | 88 | 86 |
| | | | 7.0 | 103 | 101 | 98 | 96 | 102 | 99 | 97 | 95 | 99 | 97 | 95 | 94 | 97 | 95 | 93 | 92 | 89 |
| | | | 10.0 | 105 | 103 | 101 | 99 | 103 | 102 | 100 | 99 | 101 | 99 | 98 | 97 | 98 | 97 | 96 | 95 | 92 |

