

屋内照明器具特性	
品番 (品名)	XNW2 5 3 0 WL
光源	LED3000_85_1730 x1 1730.0 lm
管理番号	K0167852 (0) DB 1
BZ分類	BZ1

器具効率		100 % 上方光束 0 % 下方光束 100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.6	76	69	64	60	75	68	64	60	74	67	63	60	72	67	63	60	59	
			0.8	84	77	72	69	83	77	72	69	81	76	72	69	80	75	71	68	67	
			1.0	89	83	78	75	88	82	78	75	86	81	77	74	84	80	76	74	72	
			0.77																		
下方投影面積 等価発光面積		c m ² c m ²	1.25	93	87	83	80	91	86	83	80	89	85	82	79	88	84	81	79	77	
			1.5	95	90	87	84	94	90	86	83	92	88	85	83	90	87	84	82	80	
			2.0	98	95	91	89	97	94	91	88	95	92	90	88	93	91	89	87	85	
取付	器具間隔最大限		2.5	100	97	94	92	99	96	94	92	97	95	92	91	95	93	91	90	88	
高さ	横方向 (A) 縦方向 (B)		3.0	102	99	96	94	100	98	96	94	98	96	94	93	96	94	93	92	89	
H m	0.71 H m 0.71 H m		4.0	103	101	99	97	102	100	98	97	100	98	97	95	98	96	95	94	92	
			5.0	104	102	101	99	103	101	100	99	101	99	98	97	99	98	97	96	93	
			7.0	105	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	95	
			10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	99	99	99	96	

