

屋内照明器具特性	
品番 (品名)	XNW2 0 3 0 B N
光源	LED5000_85_1370 x1 1370.0 l m
管理番号	K0167856 (0) DB 1
B Z 分類	B Z 1

器具効率		100 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		Z C M
下方光束		100 %																				
保守率		良 中 否	0.83	0.6	79	71	67	64	78	71	67	64	76	70	66	63	75	70	66	63	62	
			0.81	0.8	86	80	75	72	85	79	75	72	83	78	75	72	82	77	74	72	70	
			0.77	1.0	91	85	81	78	90	84	81	78	88	83	80	77	86	82	79	77	76	
				1.25	94	89	86	83	93	89	85	83	91	87	84	82	90	86	84	82	80	
下方投影面積		c m ²	1.5	97	92	89	86	96	92	88	86	94	90	88	85	92	89	87	85	83		
等価発光面積			c m ²	2.0	100	96	93	91	98	95	93	90	96	94	91	90	95	92	90	89	87	
取付 高さ	器具間隔最大限		2.5	101	98	96	94	100	98	95	93	98	96	94	92	96	94	93	91	89		
	横方向 (A)		縦方向 (B)		3.0	102	100	98	96	101	99	97	95	99	97	96	94	97	96	94	93	91
H m	0.72 H m		0.72 H m		4.0	104	102	100	99	103	101	99	98	101	99	98	97	99	97	96	95	93
					5.0	105	103	102	100	104	102	101	100	101	100	99	98	99	98	97	97	94
					7.0	106	104	103	102	105	103	102	101	102	101	101	100	100	100	99	98	96
					10.0	106	106	105	104	105	104	104	103	103	102	101	101	101	100	100	99	97

