

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NNF 5 7 5 1 0 J              |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_5000 x1 5000.0 lm |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0137117 (2) DB 1            |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ7/0.7/BZ6/0.9/BZ5          |  |  |  |  |  |  |  |  |  |

|        |         |         |               |      |     |     |      |      |     |    |      |      |    |    |      |      |    |    |     |     |
|--------|---------|---------|---------------|------|-----|-----|------|------|-----|----|------|------|----|----|------|------|----|----|-----|-----|
| 器具効率   | 100 %   | 天井      | 80 %          |      |     |     | 70 % |      |     |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|        |         |         | 壁             | 70   | 50  | 30  | 10   | 70   | 50  | 30 | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10  | 0 % |
| 上方光束   | 0 %     | 反射率     | 10 %          |      |     |     | 10 % |      |     |    | 10 % |      |    |    | 10 % |      |    |    | 0 % |     |
| 下方光束   | 100 %   |         | 床             | 10 % |     |     |      | 10 % |     |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
|        |         | 室指数     | 照明率 ( X0.01 ) |      |     |     |      |      |     |    |      |      |    |    |      |      |    |    | ZCM |     |
| 保守率    | 良       | 0.77    | 0.6           | 51   | 38  | 29  | 23   | 50   | 37  | 29 | 23   | 47   | 36 | 28 | 23   | 45   | 35 | 28 | 23  | 21  |
|        | 中       | 0.72    | 0.8           | 63   | 50  | 42  | 36   | 61   | 50  | 42 | 36   | 58   | 48 | 41 | 35   | 56   | 47 | 40 | 35  | 33  |
|        | 否       | 0.68    | 1.0           | 71   | 59  | 51  | 45   | 69   | 58  | 50 | 45   | 66   | 57 | 50 | 44   | 63   | 55 | 49 | 44  | 42  |
|        |         |         | 1.25          | 78   | 67  | 59  | 53   | 76   | 66  | 59 | 53   | 73   | 64 | 58 | 53   | 70   | 63 | 57 | 52  | 50  |
| 下方投影面積 |         |         | 1.5           | 82   | 73  | 65  | 60   | 80   | 72  | 65 | 59   | 77   | 70 | 64 | 59   | 74   | 68 | 63 | 58  | 56  |
| 等価発光面積 |         |         | 2.0           | 88   | 80  | 74  | 69   | 87   | 79  | 73 | 68   | 83   | 77 | 72 | 68   | 80   | 75 | 71 | 67  | 64  |
| 取付高さ   | 器具間隔最大限 |         | 2.5           | 92   | 85  | 80  | 75   | 90   | 84  | 79 | 75   | 87   | 82 | 78 | 74   | 84   | 80 | 76 | 73  | 70  |
|        | 横方向 (A) | 縦方向 (B) | 3.0           | 95   | 89  | 84  | 80   | 93   | 88  | 83 | 79   | 90   | 86 | 82 | 78   | 87   | 83 | 80 | 77  | 74  |
| 1.5m   | 3.47 m  | 3.38 m  | 4.0           | 98   | 93  | 89  | 86   | 96   | 92  | 89 | 85   | 94   | 90 | 87 | 84   | 91   | 88 | 85 | 83  | 80  |
| 2      | 4.66    | 4.5     | 5.0           | 100  | 96  | 93  | 90   | 99   | 95  | 92 | 89   | 96   | 93 | 90 | 88   | 93   | 91 | 88 | 86  | 83  |
| 2.5    | 5.82    | 5.63    | 7.0           | 102  | 100 | 97  | 95   | 101  | 98  | 96 | 94   | 98   | 96 | 94 | 92   | 96   | 94 | 92 | 90  | 88  |
| 3      | 6.98    | 6.69    | 10.0          | 104  | 102 | 100 | 98   | 103  | 101 | 99 | 97   | 100  | 99 | 97 | 96   | 98   | 96 | 95 | 94  | 91  |

