

# 屋内照明器具特性

品番 (品名)	NNF57511J									
光源	LED4000_85_4650 x1 4650.0 lm									
管理番号	K0137117 (2) DB1									
BZ分類	BZ7/0.7/BZ6/0.9/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	0%	反射率	10%				10%				10%				10%				0%				
下方光束	100%		床	10%				10%				10%				10%				0%			
		室指数	照明率 ( X0.01)																				ZCM
保守率	良	0.77	0.6	51	38	29	23	50	37	29	23	47	36	28	23	45	35	28	23	21			
	中	0.72	0.8	63	50	42	36	61	50	42	36	58	48	41	35	56	47	40	35	33			
	否	0.68	1.0	71	59	51	45	69	58	50	45	66	57	50	44	63	55	49	44	42			
			1.25	78	67	59	53	76	66	59	53	73	64	58	53	70	63	57	52	50			
下方投影面積		cm <sup>2</sup>	1.5	82	73	65	60	80	72	65	59	77	70	64	59	74	68	63	58	56			
等価発光面積		cm <sup>2</sup>	2.0	88	80	74	69	87	79	73	68	83	77	72	68	80	75	71	67	64			
取付高さ	器具間隔最大限		2.5	92	85	80	75	90	84	79	75	87	82	78	74	84	80	76	73	70			
	横方向 (A)	縦方向 (B)	3.0	95	89	84	80	93	88	83	79	90	86	82	78	87	83	80	77	74			
1.5m	3.47m	3.38m	4.0	98	93	89	86	96	92	89	85	94	90	87	84	91	88	85	83	80			
2	4.66	4.5	5.0	100	96	93	90	99	95	92	89	96	93	90	88	93	91	88	86	83			
2.5	5.82	5.63	7.0	102	100	97	95	101	98	96	94	98	96	94	92	96	94	92	90	88			
3	6.98	6.69	10.0	104	102	100	98	103	101	99	97	100	99	97	96	98	96	95	94	91			

