

屋内照明器具特性	
品番 (品名)	NNF 2 1 2 3 0 C
光源	LDL20S.N/11/12-K(960) ×1 960.0 1 m
管理番号	K0125039(0)DR1
BZ分類	BZ6/0.7/BZ5/8.5/BZ6

器具効率	97%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	3%	床	10%				10%				10%				10%				0%	
下方光束	94%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	5.2	4.0	3.2	2.7	5.1	3.9	3.2	2.7	4.8	3.8	3.1	2.6	4.6	3.7	3.1	2.6	2.4
	中	0.77	0.8	6.2	5.0	4.2	3.6	6.0	4.9	4.1	3.6	5.7	4.7	4.0	3.5	5.4	4.6	4.0	3.5	3.2
	否	0.68	1.0	6.8	5.7	4.9	4.3	6.6	5.6	4.8	4.2	6.3	5.4	4.7	4.2	6.0	5.2	4.6	4.1	3.9
			1.25	7.4	6.3	5.6	5.0	7.2	6.2	5.5	4.9	6.8	6.0	5.4	4.9	6.5	5.8	5.2	4.8	4.5
下方投影面積		cm ²	1.5	7.8	6.8	6.1	5.5	7.6	6.7	6.0	5.5	7.2	6.5	5.9	5.4	6.9	6.2	5.7	5.3	5.0
等価発光面積		cm ²	2.0	8.3	7.5	6.9	6.3	8.1	7.4	6.8	6.2	7.8	7.1	6.6	6.1	7.4	6.9	6.4	6.0	5.7
取付高さ	器具間隔最大限		2.5	8.7	8.0	7.4	6.9	8.5	7.8	7.3	6.8	8.1	7.6	7.1	6.7	7.8	7.3	6.9	6.5	6.2
	横方向 (A)	縦方向 (B)	3.0	8.9	8.3	7.8	7.3	8.7	8.2	7.7	7.2	8.4	7.9	7.4	7.1	8.0	7.6	7.2	6.9	6.6
1.5m	2.01 m	1.91 m	4.0	9.3	8.7	8.3	7.9	9.1	8.6	8.2	7.8	8.7	8.3	8.0	7.6	8.4	8.0	7.7	7.5	7.1
2	2.67	2.51	5.0	9.5	9.0	8.6	8.3	9.3	8.9	8.5	8.2	8.9	8.6	8.3	8.0	8.6	8.3	8.1	7.8	7.5
2.5	3.33	3.12	7.0	9.7	9.4	9.1	8.8	9.5	9.2	8.9	8.7	9.2	8.9	8.7	8.5	8.9	8.7	8.4	8.3	7.9
3	4.02	3.74	10.0	9.9	9.6	9.4	9.2	9.7	9.5	9.3	9.1	9.4	9.2	9.0	8.8	9.1	8.9	8.8	8.6	8.3

