

屋内照明器具特性

品番 (品名)	LGB57629W				
光源	LED3500_70_465 x6		465.0 lm		
管理番号	K0161568(0)DB1				
BZ分類	BZ8/0.7/BZ7				

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 37%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	63%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0
	等価発光面積		c m ²	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	7.0	10.0	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	80.0	90.0	100.0	150.0
	H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m	1.48 H m

