

屋内照明器具特性

品番 (品名)	XND9 9 7 9 WWK	
光源	LED4000_80_15720 ×1	15720.0 1 m
管理番号	K0155312 (0) DB 1	
BZ分類	BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	0 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	100 %		室指数	照明率 (X0.01)																			
保守率	良	0.76	0.6	78	71	66	62	77	70	66	62	76	69	65	62	74	69	65	62	61			
	中	0.72	0.8	85	78	74	70	84	78	73	70	82	77	73	70	81	76	72	70	68			
	否	0.64	1.0	89	83	79	76	88	83	79	75	86	82	78	75	85	80	77	75	73			
			1.25	93	88	84	80	92	87	83	80	90	86	82	80	88	84	82	79	78			
下方投影面積	c m ²		1.5	96	91	87	84	94	90	86	83	92	88	85	83	90	87	84	82	80			
			2.0	99	95	91	89	98	94	91	88	95	92	90	87	93	91	88	86	85			
取付高さ	器具間隔最大限		2.5	101	97	94	92	99	96	94	91	97	95	92	90	95	93	91	89	87			
	横方向 (A)	縦方向 (B)	3.0	102	99	96	94	101	98	96	94	98	96	94	92	96	94	93	91	89			
H m	1.16 H m	1.16 H m	4.0	104	101	99	97	102	100	98	97	100	98	97	95	98	96	95	94	92			
			5.0	105	103	101	99	103	102	100	99	101	100	98	97	99	98	97	96	93			
			7.0	106	104	103	102	105	103	102	101	102	101	100	99	100	99	98	98	95			
			10.0	107	106	105	104	105	104	104	103	103	102	102	101	101	100	100	99	96			

