

屋内照明器具特性

品番 (品名)	LGB16021AZ														
光源	LDA4L-H-E17/E/S/W/2 x1 440.0 1m														
管理番号	K0170216(0)DR1														
BZ分類	BZ5/2.8/BZ4														

器具効率	96%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	0% 96%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	54	42	34	29	52	41	34	29	50	40	33	29	48	39	33	28	27		
		0.8	64	52	45	39	62	52	44	39	59	50	44	39	57	49	43	39	36		
		1.0	70	60	52	47	69	59	52	46	66	57	51	46	63	56	50	46	44		
		1.25	76	67	60	54	75	66	59	54	72	64	58	54	69	62	57	53	51		
下方投影面積 等価発光面積	c m ² c m ²	1.5	80	72	65	60	79	71	65	60	76	69	64	59	73	67	63	59	56		
		2.0	86	79	73	68	84	78	72	68	81	76	71	67	79	74	70	66	64		
取付 高さ	器具間隔最大限		2.5	89	83	78	74	88	82	78	74	85	80	76	73	82	78	75	72	69	
	横方向 (A) H m	縦方向 (B) H m	3.0	92	87	82	78	90	85	81	78	87	83	80	77	85	81	78	76	73	
			4.0	95	91	87	84	93	90	86	83	91	87	85	82	88	85	83	81	78	
			5.0	97	93	90	87	95	92	89	87	93	90	88	85	90	88	86	84	81	
			7.0	99	96	94	92	97	95	93	91	95	93	91	89	92	91	89	88	85	
			10.0	100	98	97	95	99	97	96	94	96	95	94	93	94	93	92	91	88	

