

屋内照明器具特性

品番 (品名)	XND9996SNK	
光源	LED5000_80_16610 x1 16610.0 1m	
管理番号	K0155307(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.76	0.6	79	71	67	63	78	71	66	63	76	70	66	63	75	69	66	63	62	
	中 0.72		0.8	86	80	75	72	85	79	75	72	83	78	75	72	82	77	74	72	70
	否 0.64		1.0	91	85	81	78	90	85	81	78	88	83	80	77	86	82	79	77	76
下方投影面積 等価発光面積	cm ²	1.25	94	89	86	83	93	89	85	83	91	88	85	82	90	86	84	82	80	
		1.5	97	92	89	86	96	92	89	86	94	90	88	85	92	89	87	85	83	
取付高さ Hm	器具間隔最大限		2.5	102	99	96	94	101	98	95	93	98	96	94	92	96	95	93	91	
	横方向 (A)	縦方向 (B)	3.0	103	100	98	96	102	99	97	96	100	98	96	94	98	96	95	93	
	0.77Hm	0.77Hm	4.0	104	102	100	99	103	101	100	98	101	99	98	97	99	98	97	96	
			5.0	105	103	102	101	104	102	101	100	102	101	99	98	100	99	98	97	
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	
			10.0	107	106	105	104	106	105	104	103	103	103	102	102	101	101	100	100	

