

屋内照明器具特性

品番 (品名)	LGB81553K															
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m															
管理番号	K0151734(0)DB1															
BZ分類	BZ5															

器具効率	98%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	9%	反射率	床	10%				10%				10%				10%				0%
下方光束	89%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否 0.67 0.63 0.56	0.6	5.5	4.4	3.6	3.1	5.4	4.3	3.6	3.1	5.0	4.1	3.4	3.0	4.7	3.9	3.3	2.9	2.7	
		0.8	6.5	5.4	4.6	4.1	6.3	5.3	4.5	4.0	5.9	5.0	4.4	3.9	5.6	4.8	4.3	3.8	3.6	
		1.0	7.1	6.1	5.3	4.8	6.9	5.9	5.2	4.7	6.5	5.7	5.1	4.6	6.1	5.4	4.9	4.5	4.2	
		1.25	7.6	6.7	6.0	5.4	7.4	6.5	5.9	5.3	7.0	6.2	5.7	5.2	6.6	6.0	5.5	5.1	4.7	
下方投影面積	c m ²	1.5	8.0	7.1	6.4	5.9	7.8	7.0	6.3	5.8	7.3	6.6	6.1	5.6	6.9	6.3	5.9	5.5	5.1	
		2.0	8.5	7.8	7.1	6.6	8.3	7.6	7.0	6.5	7.8	7.2	6.7	6.3	7.4	6.9	6.5	6.1	5.7	
取付高さ	器具間隔最大限		2.5	8.8	8.2	7.6	7.1	8.6	8.0	7.5	7.0	8.1	7.6	7.2	6.8	7.7	7.3	6.9	6.6	
	横方向 (A)	縦方向 (B)	3.0	9.1	8.5	8.0	7.5	8.8	8.3	7.8	7.4	8.4	7.9	7.5	7.2	7.9	7.6	7.2	6.9	
H m	1.25 H m	1.25 H m	4.0	9.4	8.9	8.5	8.1	9.1	8.7	8.3	7.9	8.7	8.3	8.0	7.7	8.2	7.9	7.7	7.4	
			5.0	9.6	9.1	8.8	8.4	9.3	8.9	8.6	8.3	8.9	8.5	8.3	8.0	8.4	8.2	7.9	7.7	
			7.0	9.8	9.5	9.2	8.9	9.5	9.3	9.0	8.7	9.1	8.9	8.6	8.4	8.7	8.5	8.3	8.1	
			10.0	10.0	9.7	9.5	9.3	9.7	9.5	9.3	9.1	9.3	9.1	8.9	8.8	8.9	8.7	8.6	8.4	

