

屋内照明器具特性	
品番(品名)	LGW85014SZ
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0lm
管理番号	K0126055(1)DB1
BZ分類	BZ8/4.5/BZ7/8.5/BZ8

器具効率	70%	反射率	天井	80%				70%				50%				30%				0%
	上方光束 27%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	43%	床	10%				10%				10%				10%				0%	
保守率	良 0.63 中 0.6 否 0.56	室指数	照明率 (X0.01)																ZCM	
下方投影面積	cm <sup>2</sup>	0.6	3.2	2.3	1.7	1.3	2.9	2.1	1.6	1.2	2.5	1.8	1.4	1.1	2.1	1.6	1.2	0.9	0.6	
等価発光面積	cm <sup>2</sup>	0.8	3.8	2.9	2.3	1.9	3.5	2.7	2.2	1.8	3.0	2.3	1.9	1.5	2.5	2.0	1.6	1.3	0.9	
取付高さ	器具間隔最大限	1.0	4.2	3.4	2.8	2.3	3.9	3.1	2.6	2.2	3.3	2.7	2.3	1.9	2.8	2.3	1.9	1.6	1.2	
Hm	横方向(A)	1.25	4.6	3.8	3.2	2.7	4.3	3.6	3.0	2.6	3.6	3.1	2.6	2.3	3.1	2.6	2.3	2.0	1.4	
	縦方向(B)	1.5	4.9	4.2	3.6	3.1	4.5	3.9	3.4	2.9	3.9	3.4	2.9	2.6	3.3	2.9	2.5	2.2	1.6	
		2.0	5.3	4.7	4.1	3.7	4.9	4.4	3.9	3.5	4.2	3.8	3.4	3.1	3.6	3.2	2.9	2.7	2.0	
		2.5	5.6	5.0	4.5	4.1	5.2	4.7	4.2	3.9	4.5	4.1	3.7	3.4	3.8	3.5	3.2	3.0	2.2	
		3.0	5.8	5.2	4.8	4.4	5.4	4.9	4.5	4.2	4.7	4.3	4.0	3.7	4.0	3.7	3.4	3.2	2.4	
		4.0	6.0	5.6	5.2	4.9	5.6	5.2	4.9	4.6	4.9	4.6	4.3	4.0	4.2	4.0	3.7	3.5	2.7	
		5.0	6.2	5.8	5.5	5.2	5.8	5.5	5.2	4.9	5.0	4.8	4.5	4.3	4.3	4.1	3.9	3.8	2.9	
		7.0	6.4	6.1	5.8	5.6	6.0	5.7	5.5	5.2	5.2	5.0	4.8	4.6	4.5	4.4	4.2	4.1	3.2	
		10.0	6.5	6.3	6.1	5.9	6.1	5.9	5.8	5.6	5.4	5.2	5.1	4.9	4.7	4.6	4.4	4.3	3.4	

