

屋内照明器具特性	
品番(品名)	LGW85015WZ
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1m
管理番号	K0126056(1)DB1
BZ分類	BZ8/0.7/BZ7

器具効率	76%	反射率	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	28%	室指数	床	10%				10%				10%				10%				0%	
下方光束	48%		照明率 (X0.01)																ZCM		
保守率	良 0.63	0.6 中 否 0.56	0.6	3.5	2.6	1.9	1.5	3.3	2.4	1.8	1.4	2.8	2.1	1.6	1.3	2.4	1.8	1.4	1.1	8	
	0.8		4.2	3.3	2.6	2.1	3.9	3.0	2.5	2.0	3.4	2.7	2.2	1.8	2.9	2.3	1.9	1.6	1.2		
	1.0		4.7	3.8	3.1	2.6	4.3	3.5	2.9	2.5	3.7	3.1	2.6	2.2	3.2	2.7	2.3	1.9	1.4		
	1.25		5.1	4.2	3.6	3.1	4.7	4.0	3.4	2.9	4.1	3.5	3.0	2.6	3.5	3.0	2.6	2.3	1.7		
下方投影面積	cm ²	等価発光面積	cm ²	1.5	5.4	4.6	4.0	3.5	5.0	4.3	3.8	3.3	4.4	3.8	3.3	3.0	3.7	3.3	2.9	2.6	2.0
				2.0	5.8	5.2	4.6	4.1	5.5	4.8	4.3	3.9	4.7	4.2	3.8	3.5	4.1	3.7	3.4	3.1	2.4
取付高さ	器具間隔最大限		2.5	6.1	5.5	5.0	4.6	5.7	5.2	4.7	4.3	5.0	4.6	4.2	3.9	4.3	4.0	3.7	3.4	2.6	
	横方向(A)	縦方向(B)		3.0	6.3	5.8	5.3	4.9	5.9	5.4	5.0	4.6	5.2	4.8	4.4	4.1	4.5	4.2	3.9	3.7	2.9
Hm	1.65Hm	1.65Hm	4.0	6.6	6.1	5.7	5.4	6.2	5.8	5.4	5.1	5.4	5.1	4.8	4.6	4.7	4.5	4.2	4.0	3.2	
			5.0	6.8	6.4	6.0	5.7	6.4	6.0	5.7	5.4	5.6	5.3	5.1	4.8	4.9	4.7	4.5	4.3	3.4	
			7.0	7.0	6.7	6.4	6.1	6.6	6.3	6.0	5.8	5.8	5.6	5.4	5.2	5.1	4.9	4.7	4.6	3.7	
			10.0	7.1	6.9	6.7	6.5	6.7	6.5	6.3	6.1	6.0	5.8	5.6	5.5	5.2	5.1	5.0	4.9	3.9	

