

屋内照明器具特性	
品番 (品名)	L G W 8 5 0 5 6 Z
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 l m
管理番号	K0126477(0)DR1
BZ分類	BZ9/0.7/BZ8

器具効率	82%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	41%	床	10%				10%				10%				10%				0%				
下方光束	41%	室指数	照明率 (X0.01)																				ZCM
保守率	良 0.63 中 0.6 否 0.56	0.6	37	26	20	15	33	24	18	14	27	20	15	12	22	16	12	9	5				
		0.8	43	33	27	22	40	31	24	20	32	26	21	17	26	21	17	14	8				
		1.0	48	39	32	26	44	35	29	25	36	30	25	21	29	24	20	17	10				
		1.25	53	44	37	32	48	40	34	29	40	34	29	25	32	27	23	20	13				
下方投影面積	c m ²	1.5	56	48	41	36	51	44	38	33	42	37	32	28	34	30	26	23	15				
		2.0	61	53	47	42	56	49	44	39	46	41	37	33	37	34	30	28	18				
取付高さ	器具間隔最大限		2.5	64	57	52	47	58	53	48	44	49	44	40	37	40	36	33	21				
	横方向 (A)	縦方向 (B)	3.0	66	60	55	51	61	55	51	47	51	47	43	40	41	38	36	23				
H m	1.66 H m	1.84 H m	4.0	69	64	60	56	63	59	55	52	53	50	47	44	44	41	39	25				
			5.0	70	66	63	59	65	61	58	55	55	52	49	47	45	43	41	39	27			
			7.0	73	69	66	64	67	64	62	59	57	55	53	51	47	46	44	30				
			10.0	74	72	70	67	69	67	65	63	59	57	55	54	49	48	46	32				

