

屋内照明器具特性

品番 (品名)	L G W 8 5 0 5 7 Z									
光源	LDA4 L - H - E17 / E / S / W / 2 × 1					440.0 l m				
管理番号	K0126479 (0) DR 1									
B Z 分類	BZ9 / 0.7 / BZ8									

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		41 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		42 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			Z C M	
保守率	良	0.63	0.6	37	27	20	16	34	25	19	14	28	21	16	12	22	17	13	10	5	
	中	0.6	0.8	44	34	27	22	40	31	25	20	33	26	21	17	26	21	17	14	8	
	否	0.56	1.0	49	39	32	27	45	36	30	25	37	30	25	21	29	24	20	17	10	
			1.25	53	44	37	32	49	41	34	30	40	34	29	25	32	27	24	20	13	
下方投影面積	c m ²		1.5	57	48	41	36	52	44	38	33	43	37	32	28	35	30	26	23	15	
	等価発光面積		c m ²	2.0	61	54	48	42	56	50	44	39	47	41	37	33	38	34	30	28	18
取付高さ	器具間隔最大限		2.5	64	58	52	47	59	53	48	44	49	45	41	37	40	37	33	31	21	
	横方向 (A)	縦方向 (B)	3.0	66	60	55	51	61	56	51	47	51	47	43	40	42	39	36	33	23	
H m	1.51 H m	1.54 H m	4.0	69	64	60	56	64	60	56	52	54	50	47	44	44	42	39	37	25	
			5.0	71	67	63	59	66	62	59	55	56	53	50	47	46	43	41	39	27	
			7.0	73	70	67	64	68	65	62	60	58	55	53	51	48	46	44	43	30	
			10.0	75	73	70	68	70	68	65	63	59	58	56	54	50	48	47	45	33	

