

屋内照明器具特性

品番 (品名)	S F 9 9 7 Z	
光源	LDA4L - H - E17 / E / S / W / 2 x1	440.0 lm
管理番号	K0169409 (0) DR 1	
BZ分類	BZ10	

器具効率	71 %	天井	80 %				70 %				50 %				30 %				0 %						
	上方光束		44 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
	下方光束		27 %		床	10 %				10 %				10 %				10 %				0 %			
室指数	照明率 (X0.01)																			ZCM					
保守率	良	0.67	0.6	30	21	15	12	27	19	14	10	21	15	11	8	15	11	8	5	1					
	中	0.63	0.8	36	27	21	16	32	24	19	15	25	19	14	11	18	14	10	8	2					
	否	0.56	1.0	40	31	25	20	35	28	22	18	27	22	18	14	20	16	13	10	4					
下方投影面積	等価発光面積	cm ²	1.25	43	35	29	25	39	32	26	22	30	25	21	17	22	18	15	13	5					
			1.5	46	39	33	28	41	35	30	26	32	27	23	20	24	20	17	15	6					
取付高さ	器具間隔最大限		Hm	0.00Hm	0.00Hm	Hm	0.00Hm	2.5	53	47	42	38	48	43	38	34	38	34	30	27	28	25	23	21	10
	横方向 (A)	縦方向 (B)						3.0	55	50	45	41	49	45	41	37	39	36	33	30	30	30	27	25	23
								4.0	57	53	49	46	52	48	45	41	41	38	36	33	32	29	27	26	14
								5.0	59	55	52	49	53	50	47	44	43	40	38	36	33	31	29	28	15
								7.0	61	58	55	53	55	53	50	48	45	43	41	39	35	33	32	30	17
								10.0	63	60	58	56	57	55	53	51	46	45	43	42	36	35	34	33	19

