

|          |                                 |
|----------|---------------------------------|
| 屋内照明器具特性 |                                 |
| 品番 (品名)  | XND9 9 6 9 WVK                  |
| 光源       | LED3500_80_11470 ×1 11470.0 1 m |
| 管理番号     | K0155318 ( 0 ) DB 1             |
| BZ分類     | BZ1                             |

|        |                                     |          |               |     |     |     |      |     |     |     |      |     |     |     |      |     |     |    |     |    |
|--------|-------------------------------------|----------|---------------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|----|-----|----|
| 器具効率   | 101 %                               | 天井       | 80 %          |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |     |    | 0 % |    |
|        |                                     | 壁        | 70            | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10 | 0 % |    |
| 上方光束   | 0 %                                 | 床        | 10 %          |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |    | 0 % |    |
| 下方光束   | 101 %                               | 室指数      | 照明率 ( X0.01 ) |     |     |     |      |     |     |     |      |     |     |     |      |     |     |    | ZCM |    |
| 保守率    | 良<br>中<br>否<br>0.76<br>0.72<br>0.64 | 0.6      | 78            | 70  | 66  | 62  | 77   | 70  | 65  | 62  | 75   | 69  | 65  | 62  | 74   | 68  | 65  | 62 | 61  |    |
|        |                                     | 0.8      | 85            | 78  | 74  | 70  | 84   | 78  | 73  | 70  | 82   | 77  | 73  | 70  | 81   | 76  | 72  | 70 | 68  |    |
|        |                                     | 1.0      | 89            | 83  | 79  | 76  | 88   | 83  | 79  | 75  | 86   | 82  | 78  | 75  | 85   | 80  | 77  | 75 | 73  |    |
|        |                                     | 1.25     | 93            | 88  | 84  | 80  | 92   | 87  | 83  | 80  | 90   | 86  | 82  | 80  | 88   | 84  | 82  | 79 | 77  |    |
| 下方投影面積 | c m <sup>2</sup>                    | 1.5      | 96            | 91  | 87  | 84  | 94   | 90  | 86  | 83  | 92   | 88  | 85  | 83  | 90   | 87  | 84  | 82 | 80  |    |
|        |                                     | 2.0      | 99            | 95  | 91  | 89  | 98   | 94  | 91  | 88  | 95   | 92  | 90  | 87  | 93   | 91  | 88  | 87 | 85  |    |
| 取付高さ   | 器具間隔最大限                             |          | 2.5           | 101 | 97  | 94  | 92   | 100 | 96  | 94  | 91   | 97  | 95  | 92  | 90   | 95  | 93  | 91 | 89  | 87 |
|        | 横方向 (A)                             | 縦方向 (B)  | 3.0           | 102 | 99  | 96  | 94   | 101 | 98  | 96  | 94   | 99  | 96  | 94  | 92   | 97  | 95  | 93 | 91  | 89 |
| H m    | 1.19 H m                            | 1.19 H m | 4.0           | 104 | 101 | 99  | 97   | 103 | 100 | 98  | 97   | 100 | 98  | 97  | 95   | 98  | 97  | 95 | 94  | 92 |
|        |                                     |          | 5.0           | 105 | 103 | 101 | 99   | 104 | 102 | 100 | 99   | 101 | 100 | 98  | 97   | 99  | 98  | 97 | 96  | 93 |
|        |                                     |          | 7.0           | 106 | 105 | 103 | 102  | 105 | 103 | 102 | 101  | 102 | 101 | 100 | 99   | 100 | 99  | 98 | 95  |    |
|        |                                     |          | 10.0          | 107 | 106 | 105 | 104  | 106 | 105 | 104 | 103  | 103 | 103 | 102 | 101  | 101 | 100 | 99 | 97  |    |

