

# 屋内照明器具特性

品番 (品名)	L G W 5 1 7 8 7	
光源	LED2700_70_818 x1	818.0 l m
管理番号	K0161586 ( 0 ) DB 1	
B Z 分類	BZ6 / 0.7 / BZ5 / 3.5 / BZ6 / 4.5 / BZ5 / 8.5 / BZ6	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 14 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	86 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 ( X 0.01 )																				Z C M
保守率	良	0.63	0.6	53	40	32	27	51	39	32	26	47	37	30	25	43	35	29	24	22	
	中	0.6	0.8	62	50	42	36	60	49	41	35	55	46	39	34	51	43	38	33	30	
	否	0.56	1.0	69	57	49	43	66	56	48	42	61	52	46	41	57	49	44	39	35	
			1.25	74	64	56	50	72	62	55	49	66	58	52	47	62	55	50	45	41	
下方投影面積	c m <sup>2</sup>		1.5	78	69	61	55	76	67	60	54	70	63	57	52	65	59	54	50	46	
	等価発光面積		c m <sup>2</sup>	2.0	84	76	69	64	81	74	68	62	76	69	64	60	71	65	61	57	52
取付高さ	器具間隔最大限		2.5	88	81	75	69	85	78	73	68	79	74	69	65	74	70	66	62	57	
	横方向 ( A )	縦方向 ( B )	3.0	90	84	79	74	87	82	77	72	82	77	73	69	77	73	69	66	60	
H m	1.31 H m	1.30 H m	4.0	94	88	84	80	91	86	82	78	85	81	78	75	80	77	74	71	65	
			5.0	96	91	87	84	93	89	85	82	87	84	81	78	82	79	77	75	68	
			7.0	98	95	92	89	95	92	89	87	90	87	85	83	85	83	81	79	72	
			10.0	100	98	95	93	97	95	93	91	92	90	88	86	87	85	84	82	76	

