

|          |                                 |
|----------|---------------------------------|
| 屋内照明器具特性 |                                 |
| 品番 (品名)  | XLX110DENJ                      |
| 光源       | LED5000_85_12000 ×1 12000.0 1 m |
| 管理番号     | K0154867(0)D 1                  |
| BZ分類     | BZ5                             |

|        |                                     |         |               |     |     |     |      |     |     |    |      |     |    |    |      |    |    |    |     |    |  |  |     |
|--------|-------------------------------------|---------|---------------|-----|-----|-----|------|-----|-----|----|------|-----|----|----|------|----|----|----|-----|----|--|--|-----|
| 器具効率   | 100 %                               | 天井      | 80 %          |     |     |     | 70 % |     |     |    | 50 % |     |    |    | 30 % |    |    |    | 0 % |    |  |  |     |
|        |                                     | 壁       | 70            | 50  | 30  | 10  | 70   | 50  | 30  | 10 | 70   | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |  |  |     |
| 上方光束   | 0 %                                 | 床       | 10 %          |     |     |     | 10 % |     |     |    | 10 % |     |    |    | 10 % |    |    |    | 0 % |    |  |  |     |
| 下方光束   | 100 %                               | 室指数     | 照明率 ( X0.01 ) |     |     |     |      |     |     |    |      |     |    |    |      |    |    |    |     |    |  |  | ZCM |
| 保守率    | 良<br>中<br>否<br>0.81<br>0.77<br>0.68 | 0.6     | 56            | 44  | 36  | 31  | 55   | 43  | 36  | 31 | 53   | 42  | 35 | 30 | 50   | 41 | 35 | 30 | 28  |    |  |  |     |
|        |                                     | 0.8     | 66            | 55  | 47  | 41  | 65   | 54  | 46  | 41 | 62   | 53  | 46 | 41 | 60   | 51 | 45 | 40 | 38  |    |  |  |     |
|        |                                     | 1.0     | 73            | 62  | 54  | 48  | 71   | 61  | 54  | 48 | 68   | 60  | 53 | 48 | 66   | 58 | 52 | 47 | 45  |    |  |  |     |
|        |                                     | 1.25    | 79            | 69  | 62  | 56  | 77   | 68  | 61  | 56 | 74   | 66  | 60 | 55 | 71   | 65 | 59 | 55 | 52  |    |  |  |     |
| 下方投影面積 | c m <sup>2</sup>                    | 1.5     | 83            | 74  | 67  | 61  | 81   | 73  | 67  | 61 | 78   | 71  | 65 | 61 | 75   | 69 | 64 | 60 | 58  |    |  |  |     |
|        |                                     | 2.0     | 89            | 81  | 75  | 70  | 87   | 80  | 74  | 70 | 84   | 78  | 73 | 69 | 81   | 76 | 72 | 68 | 66  |    |  |  |     |
| 取付高さ   | 器具間隔最大限                             |         | 2.5           | 92  | 86  | 81  | 76   | 91  | 85  | 80 | 75   | 88  | 83 | 78 | 74   | 85 | 81 | 77 | 73  | 71 |  |  |     |
|        | 横方向 (A)                             | 縦方向 (B) | 3.0           | 95  | 89  | 84  | 80   | 93  | 88  | 84 | 80   | 90  | 86 | 82 | 79   | 88 | 84 | 81 | 78  | 75 |  |  |     |
| 1.5m   | 1.92 m                              | 1.93 m  | 4.0           | 98  | 94  | 90  | 86   | 97  | 93  | 89 | 86   | 94  | 90 | 87 | 84   | 91 | 88 | 85 | 83  | 80 |  |  |     |
| 2      | 2.53                                | 2.54    | 5.0           | 100 | 96  | 93  | 90   | 99  | 95  | 92 | 89   | 96  | 93 | 90 | 88   | 93 | 91 | 89 | 87  | 84 |  |  |     |
| 2.5    | 3.13                                | 3.14    | 7.0           | 102 | 100 | 97  | 95   | 101 | 99  | 96 | 94   | 98  | 96 | 94 | 92   | 96 | 94 | 92 | 91  | 88 |  |  |     |
| 3      | 3.76                                | 3.77    | 10.0          | 104 | 102 | 100 | 99   | 103 | 101 | 99 | 98   | 100 | 99 | 97 | 96   | 98 | 97 | 95 | 94  | 91 |  |  |     |

