

屋内照明器具特性

| | | |
|---------|--------------------|-----------|
| 品番 (品名) | XND2061PL | |
| 光源 | LED3000_85_1425 ×1 | 1425.0 lm |
| 管理番号 | K0162466(0)DB1 | |
| BZ分類 | BZ4 | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|----------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|----|-----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | 上方光束 | | 0% | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| | 下方光束 | | 100% | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.83 | 0.6 | 60 | 49 | 42 | 37 | 59 | 48 | 42 | 37 | 57 | 47 | 41 | 36 | 55 | 46 | 41 | 36 | 35 | |
| | 中 | 0.81 | 0.8 | 71 | 60 | 53 | 48 | 69 | 60 | 53 | 48 | 67 | 58 | 52 | 47 | 64 | 57 | 51 | 47 | 45 | |
| | 否 | 0.77 | 1.0 | 77 | 68 | 61 | 56 | 76 | 67 | 60 | 55 | 73 | 65 | 60 | 55 | 71 | 64 | 59 | 55 | 53 | |
| | | | 1.25 | 83 | 74 | 68 | 63 | 82 | 74 | 68 | 63 | 79 | 72 | 67 | 62 | 76 | 70 | 66 | 62 | 60 | |
| 下方投影面積 | c m ² | | 1.5 | 87 | 79 | 73 | 68 | 85 | 78 | 73 | 68 | 83 | 76 | 71 | 67 | 80 | 75 | 70 | 67 | 65 | |
| | 等価発光面積 | | c m ² | 2.0 | 92 | 86 | 80 | 76 | 90 | 85 | 80 | 76 | 88 | 83 | 78 | 75 | 85 | 81 | 77 | 74 | 72 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 95 | 90 | 85 | 81 | 94 | 89 | 84 | 81 | 91 | 87 | 83 | 80 | 88 | 85 | 82 | 79 | 76 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 97 | 93 | 89 | 85 | 96 | 92 | 88 | 84 | 93 | 89 | 86 | 83 | 91 | 87 | 85 | 82 | 80 | |
| H m | 1.18 H m | 1.18 H m | 4.0 | 100 | 96 | 93 | 90 | 99 | 95 | 92 | 89 | 96 | 93 | 90 | 88 | 93 | 91 | 89 | 87 | 84 | |
| | | | 5.0 | 102 | 99 | 96 | 93 | 100 | 97 | 95 | 93 | 98 | 95 | 93 | 91 | 95 | 93 | 91 | 90 | 87 | |
| | | | 7.0 | 104 | 101 | 99 | 97 | 102 | 100 | 98 | 96 | 100 | 98 | 96 | 95 | 97 | 96 | 94 | 93 | 90 | |
| | | | 10.0 | 105 | 103 | 102 | 100 | 104 | 102 | 101 | 99 | 101 | 100 | 99 | 98 | 99 | 98 | 97 | 96 | 93 | |

