

| | |
|----------|-----------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | XND1531PC |
| 光源 | LED3500_85_755 x1 755.0 l m |
| 管理番号 | K0159508 (2) DB 1 |
| BZ分類 | BZ5 / 0.7 / BZ4 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|----------|------------------|-----|-----|-----|------|-----|-----|-----|------|-----|----|----|------|----|----|----|-----|----|
| 器具効率 | 100 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % | |
| 上方光束 | 0 % | 床 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | |
| 下方光束 | 100 % | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.83 | 0.6 | 58 | 46 | 38 | 33 | 57 | 45 | 38 | 33 | 54 | 44 | 38 | 33 | 52 | 43 | 37 | 33 | 31 |
| | 中 | 0.81 | 0.8 | 68 | 57 | 49 | 44 | 67 | 56 | 49 | 44 | 64 | 55 | 48 | 43 | 62 | 54 | 48 | 43 | 41 |
| | 否 | 0.77 | 1.0 | 75 | 64 | 57 | 51 | 73 | 64 | 57 | 51 | 70 | 62 | 56 | 51 | 68 | 61 | 55 | 50 | 48 |
| | | | 1.25 | 81 | 71 | 64 | 59 | 79 | 70 | 64 | 59 | 76 | 69 | 63 | 58 | 73 | 67 | 62 | 58 | 55 |
| 下方投影面積 | c m ² | | 1.5 | 85 | 76 | 70 | 64 | 83 | 75 | 69 | 64 | 80 | 73 | 68 | 63 | 77 | 72 | 67 | 63 | 61 |
| | 等価発光面積 | | c m ² | 2.0 | 90 | 83 | 77 | 73 | 89 | 82 | 77 | 72 | 86 | 80 | 75 | 71 | 83 | 78 | 74 | 71 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 94 | 88 | 82 | 78 | 92 | 86 | 82 | 78 | 89 | 84 | 80 | 77 | 86 | 82 | 79 | 76 | 73 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 96 | 91 | 86 | 82 | 94 | 90 | 85 | 82 | 92 | 87 | 84 | 81 | 89 | 85 | 82 | 80 | 77 |
| H m | 1.23 H m | 1.23 H m | 4.0 | 99 | 95 | 91 | 88 | 97 | 94 | 90 | 87 | 95 | 91 | 89 | 86 | 92 | 89 | 87 | 85 | 82 |
| | | | 5.0 | 101 | 97 | 94 | 91 | 99 | 96 | 93 | 91 | 97 | 94 | 91 | 89 | 94 | 92 | 90 | 88 | 85 |
| | | | 7.0 | 103 | 100 | 98 | 96 | 102 | 99 | 97 | 95 | 99 | 97 | 95 | 93 | 96 | 95 | 93 | 92 | 89 |
| | | | 10.0 | 104 | 103 | 101 | 99 | 103 | 101 | 100 | 98 | 101 | 99 | 98 | 97 | 98 | 97 | 96 | 95 | 92 |

