

# 屋内照明器具特性

|         |                            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XND1551PA                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_900 x1 900.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0163222(0)DB1             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ4                        |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |         |              |     |     |     |     |     |     |     |     |     |     |    |     |    |     |    |     |    |
|--------|------------------|---------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|-----|----|-----|----|
| 器具効率   | 100%             | 天井      | 80%          |     |     |     | 70% |     |     |     | 50% |     |     |    | 30% |    |     |    | 0%  |    |
|        |                  |         | 壁            | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10  | 70 | 50  | 30 | 10  | 0% |
|        |                  |         |              | 床   | 10% |     |     |     | 10% |     |     |     | 10% |    |     |    | 10% |    |     |    |
| 上方光束   | 0%               | 室指数     | 照明率 ( X0.01) |     |     |     |     |     |     |     |     |     |     |    |     |    |     |    | ZCM |    |
| 下方光束   | 100%             |         |              |     |     |     |     |     |     |     |     |     |     |    |     |    |     |    |     |    |
| 保守率    | 良<br>中<br>否      | 0.83    | 0.6          | 58  | 47  | 39  | 34  | 57  | 46  | 39  | 34  | 55  | 45  | 38 | 34  | 53 | 44  | 38 | 34  | 32 |
|        |                  | 0.81    | 0.8          | 69  | 58  | 50  | 45  | 67  | 57  | 50  | 44  | 65  | 56  | 49 | 44  | 62 | 54  | 48 | 44  | 42 |
|        |                  | 0.77    | 1.0          | 75  | 65  | 58  | 52  | 74  | 64  | 57  | 52  | 71  | 63  | 57 | 52  | 68 | 61  | 56 | 51  | 49 |
|        |                  |         | 1.25         | 81  | 72  | 65  | 60  | 80  | 71  | 65  | 59  | 77  | 69  | 64 | 59  | 74 | 68  | 63 | 59  | 56 |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 85           | 77  | 70  | 65  | 84  | 76  | 70  | 65  | 81  | 74  | 69  | 64 | 78  | 72 | 68  | 64 | 61  |    |
|        |                  | 2.0     | 91           | 84  | 78  | 73  | 89  | 83  | 77  | 73  | 86  | 81  | 76  | 72 | 83  | 79 | 75  | 71 | 69  |    |
| 取付高さ   | 器具間隔最大限          |         | 2.5          | 94  | 88  | 83  | 79  | 92  | 87  | 82  | 78  | 89  | 85  | 81 | 77  | 87 | 83  | 79 | 76  | 74 |
|        | 横方向 (A)          | 縦方向 (B) | 3.0          | 96  | 91  | 87  | 83  | 95  | 90  | 86  | 82  | 92  | 88  | 84 | 81  | 89 | 86  | 83 | 80  | 78 |
| H m    | 1.21H m          | 1.21H m | 4.0          | 99  | 95  | 92  | 88  | 98  | 94  | 91  | 88  | 95  | 92  | 89 | 86  | 92 | 90  | 87 | 85  | 82 |
|        |                  |         | 5.0          | 101 | 98  | 95  | 92  | 100 | 96  | 94  | 91  | 97  | 94  | 92 | 90  | 94 | 92  | 90 | 88  | 86 |
|        |                  |         | 7.0          | 103 | 101 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97  | 95 | 94  | 97 | 95  | 93 | 92  | 89 |
|        |                  |         | 10.0         | 105 | 103 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 99  | 98 | 97  | 98 | 97  | 96 | 95  | 92 |

