

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XND1031PE                   |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED3000_85_445 x1 445.0 l m |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0159508 (2) DB1            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5/0.7/BZ4                 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |          |                  |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |    |    |
|--------|------------------|----------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|----|----|----|----|
| 器具効率   | 100%             | 天井       | 80%              |     |     |     | 70% |     |     |     | 50% |     |    |    | 30% |    |    |    | 0% |    |
|        |                  | 壁        | 70               | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 70  | 50 | 30 | 10 | 0% |    |
| 上方光束   | 0%               | 床        | 10%              |     |     |     | 10% |     |     |     | 10% |     |    |    | 10% |    |    |    | 0% |    |
| 下方光束   | 100%             | 室指数      | 照明率 ( X0.01) ZCM |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |    |    |
| 保守率    | 良                | 0.83     | 0.6              | 58  | 46  | 38  | 33  | 57  | 45  | 38  | 33  | 54  | 44 | 38 | 33  | 52 | 43 | 37 | 33 | 31 |
|        | 中                | 0.81     | 0.8              | 68  | 57  | 49  | 44  | 67  | 56  | 49  | 44  | 64  | 55 | 48 | 43  | 62 | 54 | 48 | 43 | 41 |
|        | 否                | 0.77     | 1.0              | 75  | 64  | 57  | 51  | 73  | 64  | 57  | 51  | 70  | 62 | 56 | 51  | 68 | 61 | 55 | 50 | 48 |
|        |                  |          | 1.25             | 81  | 71  | 64  | 59  | 79  | 70  | 64  | 59  | 76  | 69 | 63 | 58  | 73 | 67 | 62 | 58 | 55 |
| 下方投影面積 | c m <sup>2</sup> |          | 1.5              | 85  | 76  | 70  | 64  | 83  | 75  | 69  | 64  | 80  | 73 | 68 | 63  | 77 | 72 | 67 | 63 | 61 |
| 等価発光面積 | c m <sup>2</sup> |          | 2.0              | 90  | 83  | 77  | 73  | 89  | 82  | 77  | 72  | 86  | 80 | 75 | 71  | 83 | 78 | 74 | 71 | 68 |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 94  | 88  | 82  | 78  | 92  | 86  | 82  | 78  | 89  | 84 | 80 | 77  | 86 | 82 | 79 | 76 | 73 |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 96  | 91  | 86  | 82  | 94  | 90  | 85  | 82  | 92  | 87 | 84 | 81  | 89 | 85 | 82 | 80 | 77 |
| H m    | 1.23 H m         | 1.23 H m | 4.0              | 99  | 95  | 91  | 88  | 97  | 94  | 90  | 87  | 95  | 91 | 89 | 86  | 92 | 89 | 87 | 85 | 82 |
|        |                  |          | 5.0              | 101 | 97  | 94  | 91  | 99  | 96  | 93  | 91  | 97  | 94 | 91 | 89  | 94 | 92 | 90 | 88 | 85 |
|        |                  |          | 7.0              | 103 | 100 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97 | 95 | 93  | 96 | 95 | 93 | 92 | 89 |
|        |                  |          | 10.0             | 104 | 103 | 101 | 99  | 103 | 101 | 100 | 98  | 101 | 99 | 98 | 97  | 98 | 97 | 96 | 95 | 92 |

