

屋内照明器具特性

品番 (品名)	NNN53820WK	
光源	LDA7L-G/D/S/K6 ×1	810.0 lm
管理番号	K0169147(0)DR1	
BZ分類	BZ4	

器具効率	45%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		45%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	2.6	2.1	1.8	1.6	2.6	2.1	1.8	1.6	2.5	2.1	1.8	1.6	2.4	2.0	1.7	1.6	1.5	
	中	0.6	0.8	3.1	2.6	2.3	2.1	3.1	2.6	2.3	2.1	2.9	2.5	2.3	2.1	2.8	2.5	2.2	2.1	2.0	
	否	0.56	1.0	3.4	3.0	2.7	2.4	3.4	2.9	2.7	2.4	3.2	2.9	2.6	2.4	3.1	2.8	2.6	2.4	2.3	
			1.25	3.7	3.3	3.0	2.8	3.6	3.3	3.0	2.8	3.5	3.2	2.9	2.8	3.4	3.1	2.9	2.7	2.6	
下方投影面積	cm ²		1.5	3.9	3.5	3.2	3.0	3.8	3.5	3.2	3.0	3.7	3.4	3.2	3.0	3.5	3.3	3.1	3.0	2.9	
	等価発光面積		cm ²	2.0	4.1	3.8	3.6	3.4	4.0	3.8	3.5	3.4	3.9	3.7	3.5	3.3	3.8	3.6	3.4	3.3	3.2
取付高さ	器具間隔最大限		2.5	4.2	4.0	3.8	3.6	4.2	3.9	3.8	3.6	4.0	3.9	3.7	3.5	3.9	3.8	3.6	3.5	3.4	
	横方向 (A)	縦方向 (B)	3.0	4.3	4.1	3.9	3.8	4.3	4.1	3.9	3.8	4.1	4.0	3.8	3.7	4.0	3.9	3.8	3.7	3.6	
Hm	1.29Hm	1.29Hm	4.0	4.4	4.3	4.1	4.0	4.4	4.2	4.1	4.0	4.3	4.1	4.0	3.9	4.2	4.0	4.0	3.9	3.7	
			5.0	4.5	4.4	4.3	4.2	4.5	4.3	4.2	4.1	4.3	4.2	4.1	4.1	4.2	4.1	4.1	4.0	3.9	
			7.0	4.6	4.5	4.4	4.3	4.5	4.5	4.4	4.3	4.4	4.4	4.3	4.2	4.3	4.3	4.3	4.2	4.1	
			10.0	4.7	4.6	4.5	4.5	4.6	4.5	4.5	4.4	4.5	4.4	4.4	4.3	4.4	4.3	4.3	4.3	4.1	

