

屋内照明器具特性

品番 (品名)	LGB10717K	
光源	LED6200_70_493 x1	493.0 lm
管理番号	K0153701(0)DB1	
BZ分類	BZ4/3.5/BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		14%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		86%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	58	47	39	34	56	46	39	34	52	43	37	33	49	41	36	32	30	
	中	0.63	0.8	68	57	50	45	66	56	49	44	61	53	48	43	58	51	46	42	39	
	否	0.56	1.0	74	64	58	52	72	63	56	52	67	60	54	50	63	57	52	48	45	
			1.25	79	71	64	59	77	69	63	58	72	65	60	56	68	62	58	54	50	
下方投影面積	c m ²		1.5	83	75	69	64	80	73	67	63	75	69	64	60	71	66	62	58	54	
	等価発光面積		c m ²	2.0	88	81	76	71	85	79	74	70	80	75	71	67	75	71	67	64	59
取付高さ	器具間隔最大限		2.5	91	85	80	76	88	83	78	74	83	78	75	71	78	74	71	68	63	
	横方向 (A)	縦方向 (B)	3.0	93	88	83	79	90	85	81	78	85	81	78	75	80	77	74	71	66	
H m	1.35 H m	1.35 H m	4.0	96	91	88	84	93	89	86	83	88	84	82	79	82	80	78	75	70	
			5.0	97	94	91	88	95	91	88	86	89	87	84	82	84	82	80	78	72	
			7.0	99	97	94	92	97	94	92	90	91	89	87	85	86	84	83	81	75	
			10.0	101	99	97	95	98	96	95	93	93	91	90	88	88	87	85	84	78	

