

屋内照明器具特性	
品番 (品名)	LSEB7006K
光源	LED2700_70_2400 x1 2400.0 lm
管理番号	K0157226(0)D 1
BZ分類	BZ6/0.7/BZ5/1.8/BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	12%	床	10%				10%				10%				10%				0%				
下方光束	88%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.69	0.6	5.3	4.0	3.2	2.7	5.1	3.9	3.2	2.6	4.7	3.7	3.0	2.5	4.4	3.5	2.9	2.5	2.2			
	中	0.67	0.8	6.2	5.0	4.2	3.6	6.0	4.9	4.1	3.5	5.6	4.6	3.9	3.4	5.2	4.4	3.8	3.3	3.0			
	否	0.63	1.0	6.9	5.7	4.9	4.3	6.6	5.6	4.8	4.2	6.1	5.3	4.6	4.1	5.7	5.0	4.4	3.9	3.6			
			1.25	7.4	6.4	5.6	5.0	7.2	6.2	5.5	4.9	6.7	5.9	5.2	4.7	6.2	5.6	5.0	4.6	4.2			
下方投影面積		cm ²	1.5	7.8	6.9	6.1	5.5	7.6	6.7	6.0	5.4	7.1	6.3	5.7	5.2	6.6	6.0	5.5	5.0	4.6			
等価発光面積		cm ²	2.0	8.4	7.6	6.9	6.3	8.1	7.4	6.7	6.2	7.6	7.0	6.4	6.0	7.1	6.6	6.1	5.7	5.3			
取付高さ	器具間隔最大限		2.5	8.8	8.0	7.4	6.9	8.5	7.8	7.2	6.8	8.0	7.4	6.9	6.5	7.5	7.0	6.6	6.2	5.8			
	横方向 (A)	縦方向 (B)	3.0	9.0	8.4	7.8	7.3	8.7	8.2	7.6	7.2	8.2	7.7	7.3	6.9	7.7	7.3	7.0	6.6	6.1			
1.5m	2.04m	2.12m	4.0	9.4	8.8	8.4	7.9	9.1	8.6	8.2	7.8	8.6	8.2	7.8	7.5	8.1	7.7	7.4	7.2	6.6			
2	2.69	2.66	5.0	9.6	9.1	8.7	8.3	9.3	8.9	8.5	8.2	8.8	8.4	8.1	7.8	8.3	8.0	7.7	7.5	6.9			
2.5	3.34	3.23	7.0	9.8	9.5	9.2	8.8	9.6	9.2	8.9	8.7	9.0	8.8	8.5	8.3	8.6	8.3	8.1	7.9	7.4			
3	3.99	3.8	10.0	10.0	9.8	9.5	9.3	9.8	9.5	9.3	9.1	9.3	9.1	8.9	8.7	8.8	8.6	8.5	8.3	7.7			

