

|          |                                     |
|----------|-------------------------------------|
| 屋内照明器具特性 |                                     |
| 品番 (品名)  | LSEW4063                            |
| 光源       | LED2700_70_924 x1 924.0 lm          |
| 管理番号     | K0161585(0)DB1                      |
| BZ分類     | BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5/6.0/BZ6 |

|                |                    |                    |                  |     |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|----------------|--------------------|--------------------|------------------|-----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率           | 100%               | 天井                 | 80%              |     |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|                |                    | 壁                  | 70               | 50  | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束           | 14%                | 床                  | 10%              |     |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 下方光束           | 86%                | 室指数                | 照明率 ( X0.01 )    |     |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率            | 良                  | 0.63               | 0.6              | 53  | 40 | 32 | 27  | 51 | 39 | 31 | 26  | 47 | 37 | 30 | 25  | 43 | 35 | 29 | 24  | 21 |
|                | 中                  | 0.6                | 0.8              | 62  | 50 | 42 | 36  | 60 | 49 | 41 | 35  | 55 | 46 | 39 | 34  | 51 | 43 | 37 | 33  | 29 |
|                | 否                  | 0.56               | 1.0              | 68  | 57 | 49 | 43  | 66 | 55 | 48 | 42  | 61 | 52 | 46 | 41  | 57 | 49 | 43 | 39  | 35 |
|                |                    |                    | 1.25             | 74  | 64 | 56 | 50  | 71 | 62 | 55 | 49  | 66 | 58 | 52 | 47  | 62 | 55 | 50 | 45  | 41 |
| 下方投影面積         | c m <sup>2</sup>   |                    | 1.5              | 78  | 69 | 61 | 55  | 76 | 67 | 60 | 54  | 70 | 63 | 57 | 52  | 65 | 59 | 54 | 50  | 45 |
|                | 等価発光面積             |                    | c m <sup>2</sup> | 2.0 | 84 | 76 | 69  | 64 | 81 | 74 | 67  | 62 | 76 | 69 | 64  | 60 | 70 | 65 | 61  | 57 |
| 取付高さ           | 器具間隔最大限            |                    | 2.5              | 88  | 80 | 74 | 69  | 85 | 78 | 73 | 68  | 79 | 74 | 69 | 65  | 74 | 69 | 66 | 62  | 57 |
|                | 横方向 (A)            | 縦方向 (B)            | 3.0              | 90  | 84 | 78 | 74  | 87 | 81 | 76 | 72  | 82 | 77 | 73 | 69  | 76 | 72 | 69 | 66  | 60 |
| H <sub>m</sub> | 1.31H <sub>m</sub> | 1.31H <sub>m</sub> | 4.0              | 94  | 88 | 84 | 80  | 91 | 86 | 82 | 78  | 85 | 81 | 78 | 74  | 80 | 77 | 74 | 71  | 65 |
|                |                    |                    | 5.0              | 96  | 91 | 87 | 84  | 93 | 89 | 85 | 82  | 87 | 84 | 81 | 78  | 82 | 79 | 77 | 74  | 68 |
|                |                    |                    | 7.0              | 98  | 95 | 92 | 89  | 95 | 92 | 89 | 87  | 90 | 87 | 85 | 83  | 84 | 82 | 80 | 79  | 72 |
|                |                    |                    | 10.0             | 100 | 97 | 95 | 93  | 97 | 95 | 93 | 91  | 92 | 90 | 88 | 86  | 87 | 85 | 84 | 82  | 76 |

