

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 7 4 U
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 l m
管理番号	K0125803(1)DB1
BZ分類	BZ9

器具効率	37%	天井	80%				70%				50%				30%				0%		
	上方光束		16%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		21%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	16	11	8	6	14	10	7	5	12	9	6	5	10	7	5	4	2	
	中	0.6	0.8	19	14	11	8	17	13	10	8	14	11	8	7	12	9	7	5	3	
	否	0.56	1.0	21	16	13	11	19	15	12	10	16	13	10	8	13	10	8	7	4	
			1.25	23	19	15	13	21	17	14	12	18	15	12	10	14	12	10	8	5	
下方投影面積	c m ²		1.5	25	20	17	15	23	19	16	14	19	16	14	12	15	13	11	10	6	
	等価発光面積		c m ²	2.0	27	23	20	18	25	21	19	17	21	18	16	14	17	15	13	12	8
取付高さ	器具間隔最大限		2.5	28	25	22	20	26	23	21	19	22	20	18	16	18	16	15	14	9	
	横方向 (A)	縦方向 (B)	3.0	29	26	24	22	27	24	22	20	23	21	19	17	19	17	16	15	10	
H m	0.00 H m	1.45 H m	4.0	30	28	26	24	28	26	24	23	24	22	21	19	20	19	18	17	12	
			5.0	31	29	27	26	29	27	26	24	25	24	22	21	21	20	19	18	13	
			7.0	32	31	29	28	30	29	27	26	26	25	24	23	22	21	20	19	14	
			10.0	33	32	31	30	31	30	29	28	27	26	25	24	23	22	22	21	16	

