

屋内照明器具特性

品番 (品名)	LGB15353															
光源	LDA13L-G/Z100E/S/W ×1 1520.0 l m															
管理番号	K0168588(0)DB1															
BZ分類	BZ7/0.7/BZ6															

器具効率	91%	天井	80%				70%				50%				30%				0%		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
上方光束	26%	床	10%				10%				10%				10%				0%		
下方光束	65%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否	0.67	0.6	4.4	3.2	2.4	1.9	4.1	3.0	2.3	1.9	3.6	2.7	2.1	1.7	3.2	2.4	1.9	1.5	1.2	
		0.63	0.8	5.3	4.1	3.4	2.8	4.9	3.9	3.2	2.7	4.4	3.5	2.9	2.5	3.9	3.2	2.7	2.3	1.8	
		0.56	1.0	5.9	4.8	4.0	3.5	5.5	4.6	3.9	3.3	4.9	4.1	3.5	3.1	4.3	3.7	3.2	2.8	2.3	
			1.25	6.4	5.4	4.7	4.1	6.1	5.2	4.5	4.0	5.4	4.7	4.1	3.7	4.8	4.2	3.7	3.4	2.8	
下方投影面積		c m ²		1.5	6.8	5.9	5.2	4.7	6.4	5.6	5.0	4.5	5.7	5.1	4.6	4.1	5.1	4.6	4.1	3.8	3.1
等価発光面積		c m ²		2.0	7.3	6.6	5.9	5.4	6.9	6.3	5.7	5.2	6.2	5.7	5.2	4.8	5.5	5.1	4.7	4.4	3.7
取付高さ	器具間隔最大限		2.5	7.7	7.0	6.4	6.0	7.3	6.7	6.2	5.7	6.5	6.0	5.6	5.3	5.8	5.5	5.1	4.8	4.1	
	横方向 (A)	縦方向 (B)	3.0	7.9	7.3	6.8	6.4	7.5	7.0	6.5	6.1	6.8	6.3	6.0	5.6	6.0	5.7	5.4	5.1	4.3	
H m	1.92 H m	1.92 H m	4.0	8.2	7.7	7.3	6.9	7.8	7.4	7.0	6.6	7.1	6.7	6.4	6.1	6.3	6.1	5.8	5.6	4.7	
			5.0	8.4	8.0	7.6	7.3	8.0	7.6	7.3	7.0	7.2	6.9	6.7	6.4	6.5	6.3	6.1	5.9	5.0	
			7.0	8.6	8.3	8.0	7.8	8.2	8.0	7.7	7.4	7.5	7.2	7.0	6.8	6.7	6.6	6.4	6.2	5.3	
			10.0	8.8	8.6	8.4	8.1	8.4	8.2	8.0	7.8	7.6	7.5	7.3	7.2	6.9	6.8	6.7	6.5	5.6	

