

# 屋内照明器具特性

|         |                   |          |
|---------|-------------------|----------|
| 品番 (品名) | XND0661PC         |          |
| 光源      | LED3500_85_315 x1 | 315.0 lm |
| 管理番号    | K0162466(0)DB1    |          |
| BZ分類    | BZ4               |          |

|        |                 |               |      |     |     |     |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    |     |
|--------|-----------------|---------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|----|----|-----|
| 器具効率   | 100%            | 天井            | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |    |    |     | 0% |    |    |     |
|        | 上方光束            |               | 0%   | 反射率 | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 70 | 50  | 30 | 10 | 0% |     |
|        | 下方光束            |               | 100% |     | 床   | 10% |     |     |     | 10% |     |     |     | 10% |     |    |    | 10% |    |    |    | 0%  |
| 室指数    |                 | 照明率 ( X0.01 ) |      |     |     |     |     |     |     |     |     |     |     |     |     |    |    |     |    |    |    | ZCM |
| 保守率    | 良               | 0.83          | 0.6  | 60  | 49  | 42  | 37  | 59  | 48  | 42  | 37  | 57  | 47  | 41  | 36  | 55 | 46 | 41  | 36 | 35 |    |     |
|        | 中               | 0.81          | 0.8  | 71  | 60  | 53  | 48  | 69  | 60  | 53  | 48  | 67  | 58  | 52  | 47  | 64 | 57 | 51  | 47 | 45 |    |     |
|        | 否               | 0.77          | 1.0  | 77  | 68  | 61  | 56  | 76  | 67  | 60  | 55  | 73  | 65  | 60  | 55  | 71 | 64 | 59  | 55 | 53 |    |     |
|        |                 |               | 1.25 | 83  | 74  | 68  | 63  | 82  | 74  | 68  | 63  | 79  | 72  | 67  | 62  | 76 | 70 | 66  | 62 | 60 |    |     |
| 下方投影面積 | cm <sup>2</sup> |               | 1.5  | 87  | 79  | 73  | 68  | 85  | 78  | 73  | 68  | 83  | 76  | 71  | 67  | 80 | 75 | 70  | 67 | 65 |    |     |
|        | 等価発光面積          |               | 2.0  | 92  | 86  | 80  | 76  | 90  | 85  | 80  | 76  | 88  | 83  | 78  | 75  | 85 | 81 | 77  | 74 | 72 |    |     |
| 取付高さ   | 器具間隔最大限         |               | 2.5  | 95  | 90  | 85  | 81  | 94  | 89  | 84  | 81  | 91  | 87  | 83  | 80  | 88 | 85 | 82  | 79 | 76 |    |     |
|        | 横方向 (A)         | 縦方向 (B)       | 3.0  | 97  | 93  | 89  | 85  | 96  | 92  | 88  | 84  | 93  | 89  | 86  | 83  | 91 | 87 | 85  | 82 | 80 |    |     |
| Hm     | 1.18Hm          | 1.18Hm        | 4.0  | 100 | 96  | 93  | 90  | 99  | 95  | 92  | 89  | 96  | 93  | 90  | 88  | 93 | 91 | 89  | 87 | 84 |    |     |
|        |                 |               | 5.0  | 102 | 99  | 96  | 93  | 100 | 97  | 95  | 93  | 98  | 95  | 93  | 91  | 95 | 93 | 91  | 90 | 87 |    |     |
|        |                 |               | 7.0  | 104 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 96  | 95  | 97 | 96 | 94  | 93 | 90 |    |     |
|        |                 |               | 10.0 | 105 | 103 | 102 | 100 | 104 | 102 | 101 | 99  | 101 | 100 | 99  | 98  | 99 | 98 | 97  | 96 | 93 |    |     |

