

# 屋内照明器具特性

品番 (品名)	XNW9090WV	
光源	LED3500_85_9020 x1 9020.0lm	
管理番号	K0164312(2)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.81	0.6	78	71	66	63	77	70	66	63	76	70	65	62	74	69	65	62	61	
	中 0.77		0.8	86	79	75	72	85	79	75	72	83	78	74	71	82	77	74	71	70
	否 0.68		1.0	91	85	81	78	90	84	81	78	88	83	80	77	86	82	79	77	75
下方投影面積	cm <sup>2</sup>	1.25	94	89	86	83	93	89	85	83	91	88	84	82	90	86	84	82	80	
		等価発光面積	cm <sup>2</sup>	1.5	97	92	89	86	96	92	88	86	94	90	88	85	92	89	87	85
取付高さ	器具間隔最大限		2.5	102	99	96	94	101	98	95	93	98	96	94	92	96	95	93	91	89
	横方向 (A)	縦方向 (B)	3.0	103	100	98	96	102	99	97	96	100	98	96	94	98	96	95	93	91
Hm	0.76Hm	0.76Hm	4.0	104	102	101	99	103	101	100	98	101	99	98	97	99	98	97	96	93
			5.0	105	104	102	101	104	103	101	100	102	101	99	98	100	99	98	97	95
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96
			10.0	107	106	105	104	106	105	104	103	103	103	102	102	101	101	100	100	97

