

屋内照明器具特性

品番 (品名)	L G W 8 5 2 1 8 Z									
光源	LDA4L - H - E17 / E / S / W / 2 × 1					440.0 l m				
管理番号	K0168589 (0) DB 1									
BZ分類	BZ7 / 0.7 / BZ8 / 4.5 / BZ7									

器具効率	54 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		13 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	41 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.63	0.6	2.6	1.9	1.5	1.2	2.5	1.8	1.4	1.1	2.2	1.7	1.3	1.0	2.0	1.5	1.2	1.0	8
	中	0.6	0.8	3.0	2.3	1.8	1.5	2.8	2.2	1.7	1.4	2.5	2.0	1.6	1.3	2.2	1.8	1.4	1.2	9
	否	0.56	1.0	3.3	2.6	2.1	1.7	3.1	2.5	2.0	1.7	2.8	2.2	1.8	1.5	2.4	2.0	1.7	1.4	11
			1.25	3.6	2.9	2.4	2.0	3.4	2.8	2.3	2.0	3.0	2.5	2.1	1.8	2.6	2.2	1.9	1.6	13
下方投影面積	c m ²		1.5	3.8	3.2	2.7	2.3	3.6	3.0	2.6	2.2	3.2	2.7	2.4	2.0	2.8	2.4	2.1	1.9	15
等価発光面積	c m ²		2.0	4.1	3.6	3.1	2.8	3.9	3.4	3.0	2.7	3.5	3.1	2.7	2.4	3.1	2.8	2.5	2.2	18
取付高さ	器具間隔最大限		2.5	4.4	3.9	3.5	3.1	4.1	3.7	3.3	3.0	3.7	3.3	3.0	2.7	3.3	3.0	2.8	2.5	2.1
	横方向 (A)	縦方向 (B)	3.0	4.5	4.1	3.7	3.4	4.3	3.9	3.6	3.2	3.9	3.5	3.2	3.0	3.5	3.2	3.0	2.7	2.3
H m	0.65 H m	0.66 H m	4.0	4.7	4.4	4.1	3.8	4.5	4.2	3.9	3.6	4.1	3.8	3.6	3.3	3.7	3.5	3.3	3.1	2.6
			5.0	4.9	4.6	4.3	4.0	4.7	4.4	4.1	3.9	4.2	4.0	3.8	3.6	3.8	3.6	3.5	3.3	2.8
			7.0	5.1	4.8	4.6	4.4	4.8	4.6	4.4	4.2	4.4	4.2	4.1	3.9	4.0	3.9	3.7	3.6	3.1
			10.0	5.2	5.0	4.8	4.7	5.0	4.8	4.7	4.5	4.6	4.4	4.3	4.2	4.2	4.0	3.9	3.8	3.3

