

屋内照明器具特性	
品番(品名)	LGWC85044AZ
光源	LDA4L-H-E17/E/S/W/2 x1 440.0 1 m
管理番号	K0125233(1)DB1
BZ分類	BZ4/0.7/BZ5

器具効率	77%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	9%	床	10%				10%				10%				10%				0%			
下方光束	68%	室指数	照明率 (X0.01)																			ZCM
保守率	良	0.63	0.6	4.5	3.6	3.0	2.6	4.3	3.5	3.0	2.6	4.1	3.4	2.9	2.5	3.8	3.2	2.8	2.5	2.3		
	中	0.6	0.8	5.1	4.2	3.6	3.2	4.9	4.1	3.6	3.1	4.6	3.9	3.4	3.1	4.3	3.7	3.3	3.0	2.7		
	否	0.56	1.0	5.5	4.7	4.1	3.6	5.3	4.6	4.0	3.6	5.0	4.3	3.9	3.5	4.7	4.1	3.7	3.4	3.1		
			1.25	5.9	5.2	4.6	4.1	5.7	5.0	4.5	4.1	5.4	4.8	4.3	3.9	5.0	4.5	4.1	3.8	3.5		
下方投影面積		cm ²	1.5	6.2	5.5	5.0	4.5	6.0	5.4	4.9	4.5	5.6	5.1	4.7	4.3	5.3	4.8	4.5	4.2	3.8		
等価発光面積		cm ²	2.0	6.6	6.0	5.5	5.1	6.4	5.9	5.4	5.0	6.0	5.6	5.2	4.8	5.7	5.3	5.0	4.7	4.3		
取付高さ	器具間隔最大限		2.5	6.9	6.4	5.9	5.5	6.7	6.2	5.8	5.4	6.3	5.9	5.5	5.2	5.9	5.6	5.3	5.0	4.6		
	横方向(A)	縦方向(B)	3.0	7.1	6.6	6.2	5.8	6.9	6.4	6.1	5.7	6.5	6.1	5.8	5.5	6.1	5.8	5.5	5.3	4.9		
Hm	1.14Hm	1.16Hm	4.0	7.3	6.9	6.6	6.3	7.1	6.8	6.4	6.2	6.7	6.4	6.1	5.9	6.3	6.1	5.9	5.7	5.3		
			5.0	7.5	7.1	6.8	6.6	7.3	7.0	6.7	6.4	6.9	6.6	6.4	6.2	6.5	6.3	6.1	5.9	5.5		
			7.0	7.6	7.4	7.2	6.9	7.4	7.2	7.0	6.8	7.0	6.9	6.7	6.5	6.7	6.5	6.4	6.2	5.8		
			10.0	7.8	7.6	7.4	7.3	7.6	7.4	7.3	7.1	7.2	7.1	6.9	6.8	6.8	6.7	6.6	6.5	6.0		

