

屋内照明器具特性	
品番 (品名)	LGW85074U
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m
管理番号	K0125803(1)DB1
BZ分類	BZ9

器具効率	37%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	16%	床	10%				10%				10%				10%				0%	
下方光束	21%	室指数	照明率 (×0.01)																ZCM	
保守率	良 中 否 0.63 0.6 0.56	0.6	16	11	8	6	14	10	7	5	12	9	6	5	10	7	5	4	2	
		0.8	19	14	11	8	17	13	10	8	14	11	8	7	12	9	7	5	3	
		1.0	21	16	13	11	19	15	12	10	16	13	10	8	13	10	8	7	4	
		1.25	23	19	15	13	21	17	14	12	18	15	12	10	14	12	10	8	5	
下方投影面積	c m ²	1.5	25	20	17	15	23	19	16	14	19	16	14	12	15	13	11	10	6	
		2.0	27	23	20	18	25	21	19	17	21	18	16	14	17	15	13	12	8	
取付高さ	器具間隔最大限		2.5	28	25	22	20	26	23	21	19	22	20	18	16	18	16	15	14	9
	横方向 (A)	縦方向 (B)	3.0	29	26	24	22	27	24	22	20	23	21	19	17	19	17	16	15	10
H m	0.00 H m	1.45 H m	4.0	30	28	26	24	28	26	24	23	24	22	21	19	20	19	18	17	12
			5.0	31	29	27	26	29	27	26	24	25	24	22	21	21	20	19	18	13
			7.0	32	31	29	28	30	29	27	26	26	25	24	23	22	21	20	19	14
			10.0	33	32	31	30	31	30	29	28	27	26	25	24	23	22	22	21	16

