

屋内照明器具特性

品番 (品名)	LGB81620									
光源	LDA4 WW- H- E17 / E / S / W / 2 ×1					440.0 1 m				
管理番号	K0170954 (0) DR 1									
BZ分類	BZ5 / 1.8 / BZ4									

器具効率	79 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	0 %	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	79 %																																																						
保守率	良 中 否	0.67	0.6	4.4	3.4	2.8	2.3	4.3	3.4	2.7	2.3	4.1	3.3	2.7	2.3	3.9	3.2	2.7	2.3	2.1																																			
		0.63	0.8	5.2	4.3	3.7	3.2	5.1	4.2	3.6	3.2	4.9	4.1	3.6	3.2	4.7	4.0	3.5	3.2	3.0																																			
		0.56	1.0	5.8	4.9	4.3	3.9	5.7	4.9	4.3	3.8	5.4	4.7	4.2	3.8	5.2	4.6	4.2	3.8	3.6																																			
			1.25	6.3	5.5	5.0	4.5	6.2	5.5	4.9	4.5	5.9	5.3	4.8	4.5	5.7	5.2	4.8	4.4	4.2																																			
下方投影面積	c m ²	1.5	6.6	5.9	5.4	5.0	6.5	5.9	5.4	5.0	6.3	5.7	5.3	4.9	6.0	5.6	5.2	4.9	4.7																																				
		2.0	7.1	6.5	6.1	5.7	7.0	6.4	6.0	5.7	6.7	6.3	5.9	5.6	6.5	6.1	5.8	5.5	5.3																																				
取付高さ	器具間隔最大限		2.5	7.4	6.9	6.5	6.2	7.3	6.8	6.4	6.1	7.0	6.6	6.3	6.0	6.8	6.5	6.2	6.0	5.8																																			
	横方向 (A)	縦方向 (B)	3.0	7.6	7.2	6.8	6.5	7.5	7.1	6.7	6.4	7.2	6.9	6.6	6.4	7.0	6.7	6.5	6.3	6.1																																			
H m	1.39 H m	1.39 H m	4.0	7.8	7.5	7.2	6.9	7.7	7.4	7.1	6.9	7.5	7.2	7.0	6.8	7.3	7.1	6.9	6.7	6.5																																			
			5.0	8.0	7.7	7.5	7.2	7.8	7.6	7.4	7.2	7.6	7.4	7.2	7.1	7.4	7.3	7.1	6.9	6.7	6.7																																		
			7.0	8.1	7.9	7.7	7.6	8.0	7.8	7.7	7.5	7.8	7.7	7.5	7.4	7.6	7.5	7.4	7.3	7.0																																			
			10.0	8.3	8.1	8.0	7.9	8.2	8.0	7.9	7.8	8.0	7.8	7.7	7.6	7.8	7.7	7.6	7.5	7.3																																			

