

屋内照明器具特性

品番 (品名)	LGB10782									
光源	LED6200_70_582 x1					582.0 lm				
管理番号	K0164332(0)D 1									
BZ分類	BZ3/0.7/BZ4/2.3/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		16%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		84%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	59	49	42	37	57	47	41	36	54	45	39	35	50	43	38	34	31	
	中	0.63	0.8	68	58	50	45	65	56	49	45	61	53	48	43	57	50	46	42	38	
	否	0.56	1.0	73	64	57	52	71	62	56	51	66	59	53	49	62	56	51	47	43	
			0.56	1.25	78	70	63	58	76	68	61	57	71	64	59	54	66	60	56	52	48
下方投影面積			1.5	82	74	67	62	79	72	66	61	74	68	63	59	69	64	60	56	51	
			2.0	87	80	74	69	84	77	72	68	78	73	68	65	73	69	65	62	57	
取付高さ	器具間隔最大限		2.5	90	84	78	74	87	81	76	72	81	76	72	69	76	72	69	66	60	
	横方向 (A)	縦方向 (B)	3.0	92	86	82	78	89	84	80	76	83	79	75	72	78	74	71	69	63	
Hm	1.30Hm	1.33Hm	4.0	95	90	86	83	92	88	84	81	86	82	79	77	80	78	75	73	67	
			5.0	96	93	89	86	93	90	87	84	88	85	82	80	82	80	78	76	69	
			7.0	99	96	93	90	95	93	90	88	90	87	85	84	84	82	81	79	72	
			10.0	100	98	96	94	97	95	93	91	91	90	88	87	86	85	83	82	75	

