

# 屋内照明器具特性

品番 (品名)	LGWJ 85101SU																
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1m																
管理番号	K0128280(0)DB1																
BZ分類	BZ5/0.7/BZ4																

器具効率	26%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01) ZCM																		
下方光束	26%																				
保守率	良 0.63 中 0.6 否 0.56	0.6	15	12	10	9	15	12	10	9	14	12	10	9	14	11	10	9	8		
		0.8	18	15	13	11	17	15	13	11	17	14	13	11	16	14	12	11	11		
		1.0	20	17	15	13	19	17	15	13	18	16	15	13	18	16	14	13	13		
		1.25	21	19	17	15	21	18	17	15	20	18	16	15	19	18	16	15	15		
下方投影面積	c m <sup>2</sup>	1.5	22	20	18	17	22	20	18	17	21	19	18	17	20	19	18	17	16		
		2.0	24	22	20	19	23	22	20	19	22	21	20	19	22	21	19	19	18		
取付高さ	器具間隔最大限		2.5	25	23	22	21	24	23	21	20	23	22	21	20	23	22	21	20		
	横方向 (A)	縦方向 (B)	3.0	25	24	23	22	25	24	22	22	24	23	22	21	23	22	22	21	20	
H m	1.20 H m	1.23 H m	4.0	26	25	24	23	26	25	24	23	25	24	23	23	24	23	23	22	22	
			5.0	26	26	25	24	26	25	25	24	25	25	24	23	25	24	24	24	23	22
			7.0	27	26	26	25	27	26	25	25	26	25	25	25	25	25	24	24	23	
			10.0	27	27	26	26	27	27	26	26	26	26	26	25	26	25	25	25	24	

