

屋内照明器具特性	
品番 (品名)	L G W C 8 5 0 2 5 Z
光源	LDA4L - H - E17 / E / S / W / 2 ×1 440.0 l m
管理番号	K0122377 ( 1 ) DB 1
B Z 分類	BZ10

器具効率	88 %	天井	80 %				70 %				50 %				30 %				0 %
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	79 %	床	10 %				10 %				10 %				10 %				0 %
下方光束	9 %	室指数	照明率 ( X0.01 )																ZCM
保守率	良 中 否 0.63 0.6 0.56	0.6	38	28	22	18	32	24	19	15	23	17	14	11	14	11	8	7	0
		0.8	44	35	29	24	38	30	25	21	27	21	18	15	16	13	11	9	0
		1.0	49	40	34	29	42	35	30	25	30	25	21	18	18	15	13	11	0
		1.25	54	45	39	34	46	39	34	30	33	28	24	22	20	17	15	13	1
下方投影面積	c m <sup>2</sup>	1.5	57	49	43	39	49	43	38	34	35	30	27	24	21	19	17	15	1
		2.0	61	55	49	45	53	48	43	39	38	34	31	28	23	21	19	18	2
取付高さ	器具間隔最大限		2.5	64	58	54	50	56	51	47	43	40	36	34	31	25	23	21	2
	横方向 (A)	縦方向 (B)	3.0	66	61	57	53	57	53	50	46	41	38	36	33	26	24	22	2
H m	0.00 H m	0.00 H m	4.0	69	65	61	58	60	56	53	50	43	41	38	37	27	26	24	3
			5.0	70	67	64	61	61	58	56	53	44	42	40	39	28	27	25	24
			7.0	72	70	67	65	63	61	59	57	46	44	43	41	29	28	27	4
			10.0	74	72	70	68	65	63	61	60	47	46	45	43	30	29	28	5

