

屋内照明器具特性

品番 (品名)	LGWJ 85101SU																
光源	LDA4L-H-E17/E/S/W/2 x1 440.0 1m																
管理番号	K0128280(0)DB1																
BZ分類	BZ5/0.7/BZ4																

器具効率	26%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	0% 26%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.63 0.6 0.56	0.6	15	12	10	9	15	12	10	9	14	12	10	9	14	11	10	9	8		
		0.8	18	15	13	11	17	15	13	11	17	14	13	11	16	14	12	11	11		
		1.0	20	17	15	13	19	17	15	13	18	16	15	13	18	16	14	13	13		
		1.25	21	19	17	15	21	18	17	15	20	18	16	15	19	18	16	15	15		
下方投影面積 等価発光面積	c m ² c m ²	1.5	22	20	18	17	22	20	18	17	21	19	18	17	20	19	18	17	16		
		2.0	24	22	20	19	23	22	20	19	22	21	20	19	22	21	19	19	18		
		2.5	25	23	22	21	24	23	21	20	23	22	21	20	23	22	21	20	19		
取付 高さ	器具間隔最大限		3.0	25	24	23	22	25	24	22	22	24	23	22	21	23	22	21	20		
	横方向 (A)	縦方向 (B)																			
H m	1.20 H m	1.23 H m	4.0	26	25	24	23	26	25	24	23	25	24	23	23	24	23	23	22	22	
			5.0	26	26	25	24	26	25	25	24	25	25	24	23	25	24	24	23	22	
			7.0	27	26	26	25	27	26	25	25	26	25	25	25	25	25	24	24	23	
			10.0	27	27	26	26	27	27	26	26	26	26	26	25	26	25	25	25	24	

